



SOUTHERN HIGHLANDS REGIONAL SHOOTING
COMPLEX (SHRSC)

Sampling & Analysis Quality Plan

2022-23 Annual Operational Monitoring Program
Summary

2022-23 Quarter 4 Monitoring Report

(FOR SAMPLING 20 JUNE 2023)

SEPTEMBER 2024

Prepared for

Office of Sport
Level 3, 6B Figtree Drive
Sydney Olympic Park NSW 2127
T: 8754 7943

By

ErSed Environmental Pty Ltd

PO Box 1124
Leichhardt NSW 2040
M: 0424 203 046
E: carl.vincent@ersed.com.au

Disclaimer

The information contained herein has been collated and prepared for the stated project or use. This information may not be applicable to other projects or for other uses and should not be used for any other purpose.

Authorship

This report has been prepared by Carl Vincent.

Qualifications and training:

MBA (Exec) Australian Graduate School of Management 2009, B.Sc. (Resource and Environmental Management), Australian National University, 1992; Certificate in Water Quality Assessment (Field Officers), University of Western Sydney, 1999; Training Certificate in Coastal Management, Southern Cross University School of Coastal Management, 2000; Environmental Systems Auditor and Lead Auditor, NCSI 2008; Certified Professional in Erosion and Sediment Control.

Document Revisions

Reference	Date	Prepared	Issued
SHRC 22-23 QTR4 ANNUAL-0-110924	11 SEPT 2024	C Vincent	Submission

Contents

Part A: Background to Monitoring Event and SAQP	5
1 Introduction	5
1.1 Background to Document	5
1.2 Structure of Document	5
2 Background information	6
2.1 Site Location	6
2.2 Current Zoning.....	7
2.3 Surrounding Land Use and Sensitive Receptors	8
2.4 Site Setting	8
3 SHRSC Description.....	11
3.1 Water Quality Structures	11
3.2 Lime Treatment and Drainage.....	12
3.3 Stopbutts and Bullet Catchers.....	13
4 Quality Assurance and Data Control	14
4.1 Data Quality Objectives (DQO) Process	14
5 Conceptual Site Models (CSM).....	17
5.1 800m Range: Conceptual Site Model (CSM)	17
5.2 50m: Conceptual Site Model (CSM).....	21
5.3 500m Range: Conceptual Site Model (CSM)	25
6 Sampling Analysis and Quality Plans.....	28
6.1 SAQP for the 800m Range.....	28
6.2 SAQP for the 50m and 500m Range	31
6.3 Visual Inspections	34
6.4 Methodology	35
6.5 Laboratory QA QC.....	37
6.6 Laboratory Methods	38
7 Site Assessment Criteria	39
7.1 Rationale for Selection of Assessment Criteria	39
Part B: Monitoring Program Implementation and Report	41
8 Monitoring Program – Implementation	41
9 Monitoring Program – Quarter 4	42
9.1 Sampling (pH) Soil, Sediments and Surface Waters	43
9.2 Six Monthly Visual Inspections.....	43
9.3 Discussion of results	43
10 Recommendations and Annual Summary	50
10.1 Recommendations and Management Actions	50
11 References	52
12 Appendices	52

List of figures

1. Site Location
2. SHRSC Zoning Plan showing SP1 Special Activities and E2 Environmental Conservation
3. Site Layout of the SHRSC
4. Lime Treatment and Drainage Details
5. Bullet Catcher and Stop Butt Detail
6. 800m Range: Conceptual Site Model (CSM)
7. 50m Range: Conceptual Site Model (CSM)
8. 50m Range Layout
9. 500m Range: Conceptual Site Model (CSM)
10. 500m Range Layout

List of tables

SAQP

1. SHRSC Information and Land Use
2. Sampling Rationale Matrix (800m Range)
3. (A, B & C) Sample plan – 800m Range
4. Sampling Rationale Matrix (50m & 500m Ranges)
5. (A, B & C) Sample plan – 50m & 500m Ranges
6. (A & B) Laboratory Methods

Monitoring report

7. Annual Operational Monitoring Program
8. Monitoring Program Schedule
9. Quarter 4 Sampling Event
10. pH Soil, Sediments and Surface Waters 50m Range
11. pH Soil, Sediments and Surface Waters 500m Range
12. pH Soil, Sediments and Surface Waters 800m Range
13. Soils - Exceedances Other Criteria
14. Waters - Exceedances Other Criteria

Appendixes: Provided separately

Appendix 1: Quarter 4 laboratory results

TABLE 15	SOIL AND SEDIMENT RESULTS - 50M
TABLE 16	SOIL AND SEDIMENT RESULTS - 500M
TABLE 17	SOIL AND SEDIMENT RESULTS - 800M
TABLE 18	SURFACE WATERS (50M, 500M & 800M)

Part A: Background to Monitoring Event and SAQP

1 Introduction

1.1 Background to Document

This report forms part of the annual monitoring program for the Southern Highlands Regional Shooting Complex (SHRSC) and support the performance of the Operational Monitoring Program as detailed within Section 5 of the SHRSC Water Cycle Management Plan.

The monitoring undertaken may also be modified on site depending on site observations or in response to recommendations made as part of previous sampling exercises.

1.2 Structure of Document

This Report has been written in general accordance with the Guidelines for Consultants reporting on Contaminated Sites (OEH 2011) and National Environment Protection (Assessment of Site Contamination) Measure (NEPM) 1999 (Amended 2013) specifically Section 4, Section 7 and Schedule B5a Guideline on Ecological Risk Assessment.

This document is presented in two parts;

Part A – Background to Monitoring Event and SAQP

Part B – Monitoring Program Implementation and Report

Including Recommendations and Annual Summary

2 Background information

2.1 Site Location

The Southern Highlands Regional Shooting Complex (SHRSC) is located in the Wingecarribee LGA on Wattle Ridge Road, approximately 5.5 km northwest of the centre of the village of Hill Top in the southern highlands of New South Wales. The catchment for the site is between the upper reaches of the Nepean River and other rivers such as the Wollondilly, Nattai, Bargo and Wingecarribee. These rivers flow into the Nepean River further to the north. See Figure 1 – Site Location.




FIGURE 1: Site Location

1,036 hectares (ha) of land has been excised from the Bargo State Conservation Area by means of the National Parks and Wildlife (Adjustment of Areas) Act 2006. The SHRSC occupies an area of approximately 16 ha within this land. The remainder of the land on the site (approximately 1,000 ha) has been retained in its existing condition as a vegetation buffer zone. This area acts as a safety zone for the SHRSC.

2.2 Current Zoning

Figure 2 presents the current zoning of the SHRSC as SP1: Special Activities – Shooting Range referenced from the NSW Department of Planning SEPP 2005. For the purposes of this contamination assessment the area within the range will therefore be considered ‘recreational and open space’.

The SP1 areas are bounded by a large parcel of land zoned E2: environmental conservation. This E2 land includes the receiving catchments of the shooting ranges from the Wattle Ridge Range to the nearest water course of Rocky Waterholes Creek. For the purposes of this SAQP the area outside the range is considered ‘recreational and open space’.




FIGURE 2: SHRSC Zoning Plan showing SP1 Special Activities and E2 Environmental Conservation

Table 1 below summarises the information relevant to the site.

TABLE 1 : SHRSC Information and Land Use

Site information	
Owner	Office of Sport
Operator	Office of Sport
Address	Wattle Ridge Rd
Lot and DP	100 DP1088254
County /Parish	Camden County, Cumbertine Parish
Local Government Area	WINGECARRIBEE
Zoning	SP1 Special Activities
Land Use (current)	Shooting range or proposed shooting range
Land Use (proposed)	Shooting range
Applicable LEP	Wingecarrabee Local Environmental Plan 1989

2.3 Surrounding Land Use and Sensitive Receptors

The site is bounded by:

- Wattle Ridge – a grazing property/residence which adjoins the site to the northwest (located approximately 2.5 km north of the existing range);
- Bargo State Conservation Area to the southwest;
- A 330 kV cleared electricity easement (Transgrid) to the southeast; and
- Wattle Ridge Road to the northeast.

Bargo State Conservation Area is located further southwest, southeast and northeast. Nattai National Park is located further to the northwest, on the opposite site of the Wattle Ridge property. Nattai National Park is accessible from the end of Wattle Ridge Road approximately 3 km away.

Sensitive receptors include Rocky Waterholes Creek, located approximately 1.5 km south of the site. The creek is a tributary of the Nattai River. The Nattai River is located approximately 7.5 km west of the site.

2.4 Site Setting

The information in the sections below with respect to the physical setting at the site and the surrounding environment has been referenced from:

NSW Sport and Recreation Southern Highlands Regional Shooting Complex Environmental Assessment (Volume 1) GHD February 2008

2.4.1 Geology

The underlying geology of the site comprises the Hawkesbury Sandstone of the Mittagong Formation (Herbert and Helby: 1980: pp256). The site lies within an outcrop of the Narrabeen group, which comprises sandstone, claystone and siltstone. The Hawkesbury sandstone overlies a Triassic shale unit – the Wianamatta Group. Geologically, the site is transitional between the Cumberland Plain of the Sydney Basin and the southern uplands.

2.4.2 Soils

The three main groups of soils that occur within the regional environment are:

- Sandstone tableland soils;
- Valley soils (sandstone derived); and
- Soils associated with nutrient rich shales and igneous rocks.

Land surfaces on the site do not appear to have been significantly reworked cut or in-filled. Some grading has been undertaken at the ranges to construct the fairways and the Stop-butts. Deeper excavations and possible import of materials has occurred as part of the construction of the retention basins.

These soil landscape types are unstable when disturbed. They are highly susceptible to mass movement, such as slides and rock falls, as well as wind and water erosion (Hazelton and Tille: 1990).

2.4.3 Topography

The (SHRSC) is characterised by relatively flat topography and is situated on spur lines that trends to the north from the Wattle Ridge Range. The spur-line occupies a position between tributaries of the Rocky Waterholes Creek. All watercourses are upper tributaries of the Nattai River. Topographically the site is transitional between the Cumberland Plain of the Sydney Basin and the southern uplands.

2.4.4 Hydrology

Review of climate data for the region indicates that there is some variability in the rainfall with the maximum mean monthly rainfall of 93.8 mm in March, while the minimum mean monthly rainfall recorded is about 43.7 mm in September. The average annual rainfall is approximately 848 mm.

Rocky Waterholes Creek, which is immediately south of the proposal location, drains directly to the Nattai River approximately 6 km to the west of the existing Hill Top Rifle Range. The Nattai River drains north to Lake Burragorang.

The Hawkesbury Nepean Catchment Management Authority has classified 98% of the Nattai River as being 'Near Intact'.

The catchment of Rocky Waterholes Creek is approximately 23.5 km², whilst the catchment of the Nattai River upstream of the junction with Rocky Waterholes Creek is approximately 240 km². The total catchment area of the Nattai River upstream of Lake Burragorang is approximately 480 km².

Given the site location and the surrounding physical environment, the site is to be designed to regulate / retain run off of the surface water and sediment from the stop butt and the range areas using site drainage measures that discharge to designated retention basins. The site design aims to minimise the net sediment load migrating off site under heavy rainfall conditions throughout the year.

2.4.5 Groundwater

The site is located within the Hawkesbury Sandstone – southeast groundwater flow system, which consists of layered aquifer system with yields ranging from less than one to 50 litres per second.

Basalt caps are expected to occur in some areas of the Mittagong Ranges, with groundwater from this horizon discharging into seeps, springs and rivers (Sydney Catchment Authority: 2006).

According to the Department of Natural Resources Groundwater Licence database, groundwater within the Hill Top area was found to be present at depths of approximately 20 metres in the sandstone aquifer.

The depth to groundwater within the aquifers is expected to be dependent on rainfall and therefore is likely to vary seasonally. However, groundwater is expected at depths greater

than 15 metres below ground level. Drilling undertaken on 12 and 13 July 2007 at the (SHRSC) location indicated no obvious groundwater table present within 50 metres below ground level. Based on the reported depth to groundwater on the site being greater than 50m below ground level, potential for surficial contaminants to impact ground water existing beneath the operational ranges is therefore considered to be of low likelihood. Groundwater assessment was therefore not considered to be necessary as part of this site assessment.

2.4.6 Surrounding Groundwater Use

The Bureau of Meteorology Australian Ground Water Explorer (<http://www.bom.gov.au/water/groundwater/explorer/map.shtml>) and the DPI Office of Water ground water data base was used to search for bores within 800m of the site.

A number of monitoring bores were reported to be located within 2-5km of the site with no water quality data available. Two stock domestic bores were reported to be located within 5km.

- GW114443
A 120m stock/domestic bore located in the Hilltop Village approximately 3.2km to the south east of the site.
- GW065725
A 122m stock/domestic bore located around Wattleridge approximately 5k to the north of the site

Based on the results of the bore search and the reported local water quality the NEPM 1999 (amended 2013) ground water investigations levels (GILs) suitable for the protection of fresh water species should therefore be adopted as the assessment criteria for this SAQP.

3 SHRSC Description

The SHRSC is a regional recreational shooting complex incorporating the existing 800 metre Hill Top Rifle Range (HTRR) and separate newly constructed facilities located approximately 700m to the North West. The HTRR has been used since the 1980s by a local club for long rifles and pistol use.

It includes:

- A 800m range consisting of a of a single target area and stop butt with multiple firing points on raised mounds located at 100m intervals. In 2018-19 the 800m range was subject to major civil works to improve and rehabilitate the stop butt and surrounds.
- Club house and out buildings
- Informal parking

The newly constructed facilities include:

- A (500 metres by 100 metres) shooting range consisting of a single firing point and multiple target points set in front of intermediate mounds. A final large stop butt is provided at the end of the range;
- A (50 metres by 115 metres) shooting range consisting of 6 separated galleries each single firing point and large stop butt;
- Supporting facilities and infrastructure, including:
 - Range control and Toilet facilities;
 - Access roads (designed for two-wheel drive vehicle access) connecting to Wattle Ridge Road and between the ranges;
 - Diesel generator, solar panels, water supply tanks and septic system;
 - Informal parking for 160 cars; and
 - Basins to contain water for water quality control purposes.
- Future facilities include:
 - A (200 metres by 85 metres) shooting range;
 - A shotgun range;
 - An indoor air range (21 metres by 17 metres by 6.5 metres); and
 - A Clubhouse

Environmental controls are included in the design for the ranges at the SHRSC. These specific environmental controls are discussed following.

3.1 Water Quality Structures

A single pond or informal retention structure is located to the east of the 800m range primarily taking water from the access road adjacent to the range.

Four water quality structures/ retention basins have been constructed as part of the development of the of the 50m, 200m (yet to be built) and 500m ranges. A fifth Structure is proposed as part of a future shot gun range.

Additionally, works have been undertaken to modify an existing pond/structure located near the gate to the new ranges from Wattle Ridge Road. All structures above will be referred to in this Plan as “basins” including the informal ponds.

Figure 3 shows the layout at the SHRSC. Range and basin numbers are also indicated.




FIGURE 3: Site Layout of the SHRSC

3.2 Lime Treatment and Drainage

As part of the rehabilitation works to the 800m range and construction of the 500m and 50m ranges improved drainage measures were included. This drainage consists of a network of sub soil drainage trenches set down gradient of primary impact areas leading to lime treatment pits to raise pH and reduce the transport of heavy metals from the range areas. Stormwater lines from these treatment pits either lead to formal outlet measures or to new basins.

The 800m range has an additional pit to retain water/sediment for testing purposes as is the case for the basins at the 50 and 500 ranges. Lime pits and directional pits do not retain water.

4 Quality Assurance and Data Control

4.1 Data Quality Objectives (DQO) Process

The DQO process is a seven (7) process applied to optimise the design of the sampling and analysis and to ensure that all objectives of the investigation are met.

DQOs have been developed to detail the type of data that is needed to meet the overall objectives of this project. The DQOs presented in this document have been developed consistent with the following published guidance;

- National Environment Protection Council (1999) National Environmental Protection Measure 1999 as amended 2013 – Assessment of Site Contamination. Schedule B(2) Guideline on Site Characterisation (NEPC 2013);
- NSW DECC (2007) Guidelines for the Assessment and Management of Groundwater Contamination;
- NSW DECC (2006) Guidelines for the NSW Site Auditor Scheme (2nd Edition);
- NSW EPA (1995) Sampling Design Guidelines;
- NSW EPA (2000) Guidelines for Consultants Reporting on Contaminated Sites;
- Australian/New Zealand Standard, AN/NZS 4360:2004, Risk Management – Principles and guidelines; and
- Australian/New Zealand Standard, AN/NZS 5667.11:1998, Water Quality – Sampling - Guidance on sampling of ground waters.

The seven (7) steps are outlined, as follows:

Step 1: State the Problem – concisely describe the problem to be studied. Review prior studies and existing information to gain a sufficient understanding to define the problem;

Previous assessments, range design and current usage indicate potential contamination issues associated with the stop butt and immediate surrounds, primary and secondary shot fall areas AND drainage pathways.

Further investigation is needed to confirm the location, nature and extent of contamination (if present) and to determine what further action may be required.

Step 2: Identify the Decision – identify what questions the study will attempt to resolve, and what actions may result;

The primary question(s) that this investigation will attempt to resolve are

What are the characteristics of any contamination if present in the range and surrounds?
Is further action e.g. a risk assessment or Remediation Action Plan (RAP) required to address any contamination issues?
Are additional works required to respond to ongoing contamination and mitigate any risk to the surrounding environment?

Step 3: Identify the Inputs to the Decision – identify the information that needs to be obtained and the measurements that need to be taken to resolve the decision statement;

The locations for sampling are presented in a Sampling Rationale Matrix for each range (see Sect 6).

The contaminants of potential concern in soil/sediment/water have been selected based on the

past and use as a shooting facility.

Contaminants of potential concern are presented in the list of Analytes within the SAQP Tables for each range (see Section 6.0)

Results will be assessed against the following guidelines

ANZECC 2000 Water Quality and Sediment Quality Guidelines and

NEPM 1999 (amended 2013) Health Investigation Levels (HILs) and Ecological Investigation Levels (EILs) for Soil.

(HILs) C. Parks, recreational open space and playing fields: includes secondary schools.

(HILs) D. Commercial/Industrial: includes premises such as shops and offices as well as factories and industrial sites.

NEPM (2013) HIL D criteria do not appear to be applicable on the site and have been referenced for information purposes only. The site is zoned SP1 Special Activities for the purposes of a shooting range under the State Environmental Planning Policy (State Significant Precincts) 2005. There are areas outside the ranges themselves within the SHRSC that are zoned E2 Environmental Conservation.

Specific investigation levels for the contaminants of potential concern are presented in Section 6 Site Assessment Criteria

Step 4: Define the Study Boundaries – specify the time periods and spatial area to which decisions will apply. Determine when and where data should be collected;

The investigation is confined to range areas including fairway, rear of stop butt and associated drainage as shown in Figure 3.

No investigation will be conducted outside of the site boundaries as the areas of concern are on top of a spur line/hill and contaminant migration has been limited vertically and horizontally by design layout and area usage.

Soil sampling will be conducted around the face of the stop butt plus from areas immediately down gradient from areas which receive bullet impacts.

Sampling will also be undertaken down gradient of the stop butt in overland/surface flow lines and within the area at the rear of the stop butt where surface water exits the site.

Samples will be collected surrounding bushland areas in close proximity to the ranges

Water and Sediments will be taken from basins within the SHRC in addition to adjacent creeks off the range but where these can be readily accessed below the outlet points of the basins.

Step 5: Develop a Decision Rule – define the statistical parameter of interest, specify the action level, and integrate the previous DQO outputs into a single statement that describes the logical basis for choosing among alternative actions;

The proposed sampling density/frequency across the subject assessment area has not been strictly prepared to comply with the NSW EPA sampling density guidelines based on the assessment area.

The sampling strategy is based on previous assessments of site condition, range design, knowledge of site use and shot fall and the condition of the surrounding environment. The strategy is therefore considered sufficient to characterize contaminant impacts at the area in general accordance with the NSW EPA Sampling Design Guidelines.

The sampling frequency is acceptable for the purposes of site audit as it is in general accordance with the NSW EPA Sampling Design Guidelines.

Additional targeted sampling may be undertaken based on site observations during the site inspection;

If the contaminants in the soil outside defined shot fall areas are identified above the adopted assessment criteria then the soil should be considered as potentially contaminated and then either subjected to further risk assessment AND/OR remediated AND/OR managed accordingly.

If concentration of contaminants in sediments or water samples is identified above the adopted assessment criteria then the sampled areas should be considered as potentially contaminated and then managed accordingly. Augmentation of drainage from the stop butt area should be considered.

Step 6: Specify Tolerable Limits on Decision Errors – define the decision maker's tolerable decision error based on a consideration of the consequences of making an incorrect decision.

Data generated during this project must be appropriate to allow decisions to be made with confidence.

The potential decision errors must be identified, the potential consequences evaluated and the severity of decision error consequences assessed, the null hypothesis must be defined and what level of false positive or false negative decision error will be acceptable for the site assessment must be specified.

Considering the current and ongoing use as a recreational shooting range it has been determined that the two decision errors for the contaminants of concern are:

Type I error – deciding that site soils are within the assessment criteria when they truly are not; and

Type II error – deciding that site soils exceed the assessment criteria when they truly do not.

The consequences of deciding that the soils exceed the assessment criteria when they truly do not, will be further human health and/or ecological risk assessment and/or active remediation/management of site soils.

The consequences of deciding that the soils do not exceed the remediation acceptance criteria when they truly do, will be that contaminated soils will be left unmanaged on the site and may potentially endanger human health or pose ongoing risks to the environment. Additionally, the owners of the site may be liable for future damages and environmental clean-up costs.

For site soils, sediments and water and for each respective contaminant of concern, the baseline condition or null hypothesis is “the soils/sediments/water levels exceed the assessment criteria”. The alternative hypothesis is “the soils/sediments/water levels are within the assessment criteria”.

It is noted that the past and ongoing use of the site is such that contamination is expected and that ongoing contamination of specific areas will be unavoidable. As such management of the site as a potentially contaminated area is the default approach.

Samples will be analysed at a National Association of Testing Authorities (NATA) Accredited Laboratory and as per the laboratory's Quality Assurance targets.

Step 7: Optimise the Design – evaluate information from the previous steps and generate alternative data collection designs. Choose the most resource-effective design that meets all DQOs.

The proposed data collection design has been described in Section 6: SAQP and is expected to satisfy the DQOs.

Targeted sampling will be conducted to accurately define the lateral and vertical extent of contaminants expected at the site.

5 Conceptual Site Models (CSM)

5.1 800m Range: Conceptual Site Model (CSM)

The figure below provides a schematic CSM for the 800m range target area and surrounds. The CSM below aims to identify the following aspects relevant to the 800m range, they are:

- Areas of potential concern;
- Contaminants of potential concern;
- Potential contaminant exposure or migration pathways; and the
- Human and/or ecological receptors.

Additional elements of the CSM are discussed in the sections following.




FIGURE 6: 800m Range: Conceptual Site Model (CSM)

5.1.1 Existing infrastructure and layout

Stop butt and target area

The primary potential area of concern identified at the 800m range is the target area, stop butt, bullet catcher, and surrounds.

The 800m range target area consists of target frames which are manually controlled from within a safe ~3m deep trench (or gallery). This gallery provides access to the stop butt for maintenance and is set below the line of fire.

In-front of the gallery there is a smaller mound or mantlet running the full length of the gallery and the target area. The purpose of this mantlet is to capture low projectiles and low ricochets, to protect the gallery from repeated strikes and protect the back side of the gallery by defining the firing line for targets so that it is backed by the stop butt.

At the rear of the gallery, a large earthen mound forms the stop butt. Directly behind the targets gravel filled boxes or bullet catchers are set on the face of the stop butt. These boxes act to capture bullet strikes after they have passed through the targets.

In addition, there are multiple firing mounds along the range spaced at 100m intervals set at 100-800m from the target area. A defined firing area used by pistol shooters is located on flat ground at approximately 25m from the targets.

A gallery area has been provided in-front of the stop butt face.

Formal and informal drainage system

A secondary area of potential concern identified at the 800m range is the new drainage system from the stop butt leading off site to the South East.

The rear area of the stop butt drains via a single channel to the south. This channel discharges over a flat area located 100-110m to the rear of the targets. Water then makes its way to natural drainage channels and upper tributaries of Rocky Waterholes Creek.

5.1.2 Sources of contamination and potential contaminants of concern

The OEMP for the SHRSC requires record keeping of the number of rounds /volume of bullets fired and the type of bullets fired so that annual estimates of shot fall can be calculated for each range for management purposes.

The 800m range is designed so that all bullets strike the mantlet face or the stop butt behind the target into the bullet catchers. These are the primary impact areas.

The material at the primary impact areas of the 800m range are able to be removed and sifted to remove bullet fragments or relocated for further treatment and/or removed from site as part of maintenance activities.

It is possible that some bullets may be fired over the stop butt entirely or similarly into the intermediate firing mounds along the range length prior to the target area (the secondary impact areas) however given this is a supervised range, this loss should be in very low volumes.

A broad suite of sample analytes was proposed within this SAQP given the potential variety of ammunition used at the range. However, the primary contaminant of concern at the 800m range is considered to be Lead (Pb). Lead is the predominant constituent of ammunition shot used in most higher calibre rifles which have been used at the range.

The nominated suite of analytes for this site assessment is presented in Section 6.1 Tables

3A, B & C.

5.1.3 Identified contaminant migration pathways

The primary process for migration of contaminants from the stop butt and surrounds is identified to be via surface runoff and infiltration into the subsurface. Maintenance of stable ground cover over the surface acts to minimise potential for generation of dust from the area and also reduce potential for erosion and mobilisation of sediments. Maintenance may also include application of ameliorants to maintain a stable soil pH.

The CSM indicates the current pathways for surface water movement:

- The stop-butt benches and gallery drains as to the south east via new formal drainage infrastructure including subsoil drains, pits and open drains.
- Surface water runoff from the mantlet and the area immediately in front flows with other surface water from the range area to various points at the range perimeter.
- The area at the rear of the stop butt drains to the south via an open channel.
- Surface water at the side of the target area flows to the perimeter of the range.

The potential exists for leaching and vertical migration of contaminants into the subsurface from the primary and secondary shot fall areas. This potential is mitigated by the design of the gravel bullet catcher at the primary shot fall area which moves water more quickly to the formal drainage.

Depth to ground water is not known at the 800m range however based on the environmental assessment undertaken prior to construction of the SHRSC, groundwater is considered unlikely to be impacted by the contaminants of potential concern on the site. Therefore impacts on sources of potential water supply are not a consideration and as such Groundwater Investigations (GILs) for Fresh Waters will be used as the assessment level for management response.

5.1.4 Identified exposure routes

Three possible human exposure routes have been identified for the lead shot present at the range, they are:

- Direct contact by range users with lead impacted soils and shot
- Migration/infiltration of lead impacted surface water into retention ponds/basins and recreational water resources;
- Inhalation/ingestion of airborne lead impacted dust.

Direct contact

Two shot fall areas have been identified where direct contact (includes ingestion or absorption through the skin) with lead present in soil or shot by range users is possible where areas are not managed.

The primary impact areas where direct shot is received are the stop-butt face and the face of the mantlet. The secondary areas impact areas are the gallery and the areas in front of the mantlet. These areas in are shown on the CSM diagram.

Surface Water migration

Runoff and infiltration of rainwater that becomes impacted with lead could potentially have a low level impact on nearby downgradient surface water receptors however specific site

drainage and water quality measures have been included in the design of the SHRSC to address and mitigate this potential.

Airborne dust ingestion/inhalation

Soil particles contaminated with lead around shot fall areas can become dry and be mobilized by wind events to either migrate off site or be ingested/inhaled by range users where areas are not managed.

5.1.5 Identified Receptors

The number of potential receptors identified are consistent between all the ranges at the SHRC:

- The SHRSC is situated within the Bargo State Conservation Area and is next to Nattai National Park which are known recreational areas and are home to local flora and fauna.
- The SHRSC is situated on a ridge line and drains to multiple drainage lines in the upper catchment. These are tributaries to Rocky Waterholes Creek which is a potential recreational water resource.
- SHRSC users and the general public visit the facility under supervised management protocols.

Receptor exposure will be managed under the OEMP which will take into account the specific shot fall patterns, ground cover requirements and direction of surface water movement at each range.

Site access restrictions and maintenance of suitable ground cover at the areas of potential concern will reduce the likelihood of direct human exposure to contaminants at the source.

5.2 50m: Conceptual Site Model (CSM)

The figure below provides a schematic CSM for the 50m range target area and surrounds. The CSM below aims to identify the following aspects relevant to the 50m range, they are:

- Areas of potential concern;
- Contaminants of potential concern;
- Potential contaminant exposure or migration pathways; and the
- Human and/or ecological receptors.

Additional elements of the CSM are discussed in the sections following.




FIGURE 7 - 50m: Conceptual Site Model (CSM)

5.2.1 Existing infrastructure and layout

Stop butt and target area

The primary potential areas of concern identified at the 50m range are the target area, stop butt, bullet catcher, and surrounds.

The 50m Range consists of a five individual ranges separated by concrete dividing walls each with a single line of firing positions and a single stop butt behind the targets. The individual ranges are designed for varying uses; four are fully enclosed with gravel on the floor. The fifth range is more open with a grassed surface.

Behind the targets, a gravel filled bullet catcher is proved at the face of the stop butt.

Formal and informal drainage system

A secondary area of potential concern identified at the 50m range is the new drainage system from in front of the stop butt leading to Basin 5.

It is possible that some shot fall will occur within the floor area of the ranges.

Refer to Figure 8 for the current 50m Range layout.




FIGURE 8 - 50m Range Layout

5.2.2 Sources of contamination and potential contaminants of concern

The 50 and 500m ranges are used by recreational and competitive shooters. The OEMP for the SHRSC requires record keeping of the number of rounds /volume of bullets fired and the type of bullets fired so that annual estimates of shot fall can be calculated for each range for management purposes.

The 50m range is designed so that all bullets strike the stop butt behind the target into the bullet catchers. These are the primary impact areas. Other areas within the range (e.g. the range floor) may receive bullet fall, ricochet or skip from the primary impact area. These are indicated as secondary impact areas on Figure 7.

The butt and bullet catcher at the 50m is designed to prevent the skipping of bullets or fragments to the rear of the butt. Ongoing sampling includes the rear of the stop-butt to confirm the effectiveness of design. It is possible that some bullets may be fired over the stop-butt entirely however, given this is a supervised range this loss should be in very low volumes.

The material at the primary impact areas of the 50m range are able to be removed and sifted to remove bullet fragments or relocated for further treatment and/or removed from site as part of maintenance or construction activities.

The type of bullets will be used to confirm the range of analytes for ongoing sampling. A broad suite of sample analytes is proposed within this SAQP given the potential variety of ammunition used at the range. However, the primary contaminant of concern at the range is considered to be Lead (Pb).

The suite of analytes is presented in Section 6.2 Tables 5A, B & C

5.2.3 Identified contaminant migration pathways

The primary process for migration of contaminants from the primary and secondary impact areas and surrounds would be via surface runoff and potentially leaching to ground water. Maintenance of stable ground cover over the surface acts to minimise potential for generation of dust from the area and also reduce potential for erosion and mobilisation of sediments. Maintenance may also include application of ameliorants to maintain a stable soil pH.

The CSM diagram indicates the pathways for surface water movement:

- A collection trench runs in-front of the stop butt of the 50m Range which directs surface water via a pipe to the lime treatment pit and then to the water quality basin
- No surface water from possible shot-fall areas (primary and secondary) is able to bypass the drainage to the Water Quality Basins.
- The new water quality basin has stable gabion spillways. The basins discharge to the natural catchment and then ultimately to the tributaries of Rocky Water Holes Creek.

The potential exists for leaching and vertical migration of contaminants into the subsurface from the primary and secondary shot fall areas. This potential is mitigated by the design of the gravel bullet catcher at the primary shot fall area which moves water more quickly to the formal drainage.

Environmental Assessment undertaken prior to the construction of the SHRSC presented that groundwater is expected at depths greater than 15m and likely greater than 50m (Refer to 2.4.5 Groundwater). Therefore impacts on sources of potential water supply are not a consideration and as such Groundwater Investigations (GILs) for Fresh Waters will be used as the assessment level for management response.

5.2.4 Identified exposure routes

Three possible human exposure routes have been identified for the lead shot present at the range, they are:

- Direct contact by range users with lead impacted soils and shot
- Migration/infiltration of lead impacted surface water into retention ponds/basins and recreational water resources;
- Inhalation/ingestion of airborne lead impacted dust

Direct contact

Two impact areas have been identified where direct contact (includes ingestion or absorption through the skin) with lead present in soil or shot by range users is possible where areas are not managed.

The primary impact areas where direct shot is received are the stop-butts and the face of the mantlet.

The secondary impact areas are the floor of the range especially in front of the target area and potentially at the rear of the stop butts. These areas are shown on the CSM diagram.

Surface Water migration

Runoff and infiltration of rainwater that becomes impacted with lead could potentially have a low-level impact on nearby downgradient surface water receptors however specific site drainage and water quality measures have been included in the design of the SHRSC to address and mitigate this potential.

Airborne dust ingestion/inhalation

Soil particles contaminated with lead around shot fall areas can become dry and be mobilized by wind events to either migrate off site or be ingested/inhaled by range users where areas are not managed.

5.2.5 Identified Receptors

The number of potential receptors identified are consistent between all the ranges at the SHRSC:

- The SHRSC is situated within the Bargo State Conservation Area and is next to Nattai National Park which are known recreational areas and are home to local flora and fauna.
- The SHRSC is situated on a ridge line and drains to multiple drainage lines in the upper catchment. These are tributaries to Rocky Waterholes Creek which is a potential recreational water resource.
- SHRSC users and the general public visit the facility under supervised management protocols.

Receptor exposure will be managed under the OEMP which will take into account the specific shot fall patterns, ground cover requirements and direction of surface water movement at each range.

Site access restrictions and maintenance of suitable ground cover at the areas of potential concern will reduce the likelihood of direct human exposure to contaminants at the source.

5.3 500m Range: Conceptual Site Model (CSM)

The figure below provides a schematic CSM for the 500m range target area and surrounds. The CSM below aims to identify the following aspects relevant to the 50m range, they are:

- Areas of potential concern;
- Contaminants of potential concern;
- Potential contaminant exposure or migration pathways; and the
- Human and/or ecological receptors.

Additional elements of the CSM are discussed in the sections following.




FIGURE 9 - 500m: Conceptual Site Model (CSM)

5.3.1 Existing infrastructure and layout

Stop butt and target area

The primary potential areas of concern identified at the 500m range are the target areas, stop butt & intermediate mound, bullet catcher and surrounds.

The 500m is a single range consists of a single firing point and multiple (x6) mounds and target points set along the range length with a 7th Primary stop butt at the end of the range.

A gravel filled bullet catcher is proved at the face of the stop butt.

It is expected that significant shot fall will occur within the floor area of the range and into the intermediate target mounds.

Formal and informal drainage system

A secondary area of potential concern identified at the 500m range is the new drainage

system from the stop butt and intermediate mound.

Surface water from the 500m range fairway flows to strip drains set at the rear of the intermediate target mounds and at the toe of the stopbutt face. These drains then are connected via pipes to either of the two water quality basins.

Refer to Figure 10 for the for the current 500m Range layout.




FIGURE 10 - 500m Range Layout

5.3.2 Sources of contamination and potential contaminants of concern

The 500m range is used by recreational and competitive shooters. The OEMP for the SHRSC requires record keeping of the number of rounds /volume of bullets fired and the type of bullets fired so that annual estimates of shot fall can be calculated for each range for management purposes.

The 500m range and its use are designed so that bullets strike the intermediate target mounds and the final stop butt at the end of the range. Significant shot fall is expected between the intermediate mounds and into the fairway. These are the primary impact areas.

It is possible that some bullets may be fired over the stop butt entirely or into adjacent off range areas. These are the secondary impact areas.

The butt at the 500m is designed to prevent the skipping of bullets or fragments to the rear of the butt. Ongoing sampling includes the rear of the stop-butt to confirm the effectiveness of design. It is possible that some bullets may be fired over the stop-butt entirely however, given this is a supervised range this loss should be in very low volumes.

The material at the bullet catcher at face of the stopbutt is able to be removed and sifted to remove bullet fragments or relocated for further treatment and/or removed from site as part of maintenance activities.

The type of bullets will be used to confirm the range of analytes for ongoing sampling. A broad suite of sample analytes is proposed within this SAQP given the potential variety of ammunition used at the range. However, the primary contaminant of concern at the range is considered to be Lead (Pb). The suite of analytes is presented in Section 6.2 Tables 5A, B & C

5.3.3 Identified contaminant migration pathways

The primary process for migration of contaminants from the primary and secondary impact areas and surrounds would be via surface runoff and potentially leaching to ground water. Maintenance of stable ground cover over the surface acts to minimise potential for generation of dust from the area and also reduce potential for erosion and mobilisation of sediments. Maintenance may also include application of ameliorants to maintain a stable soil pH.

The CSM diagram indicates the pathways for surface water movement:

- Strip drains in-front of the stop butt of the 500m Range which directs surface water via a pipe to the lime treatment pit and then to the water quality basin
- No surface water from possible shot-fall areas (primary and secondary) is able to bypass the drainage to the Water Quality Basins.
- The new water quality basins have stable gabion spillways. The basins discharge to the natural catchment and then ultimately to the tributaries of Rocky Water Holes Creek.

The potential exists for leaching and vertical migration of contaminants into the subsurface from the primary and secondary shot fall areas. This potential is mitigated by the design of the gravel bullet catcher at the stopbutt and at the drainage within the primary shot fall areas which moves water more quickly to the formal drainage.

Environmental Assessment undertaken prior to the construction of the SHRSC presented that groundwater is expected at depths greater than 15m and likely greater than 50m (Refer to 2.2.5 Groundwater). Therefore impacts on sources of potential water supply are not a consideration and as such Groundwater Investigations (GILs) for Fresh Waters will be used as the assessment level for management response.

5.3.4 Identified Receptors

The number of potential receptors identified are consistent between all the ranges at the SHRSC:

- The SHRSC is situated within the Bargo State Conservation Area and is next to Nattai National Park which are known recreational areas and are home to local flora and fauna.
- The SHRSC is situated on a ridge line and drains to multiple drainage lines in the upper catchment. These are tributaries to Rocky Waterholes Creek which is a potential recreational water resource.
- SHRSC users and the general public visit the facility under supervised management protocols.

Receptor exposure will be managed under the OEMP which will take into account the specific shot fall patterns, ground cover requirements and direction of surface water movement at each range.

Site access restrictions and maintenance of suitable ground cover at the areas of potential concern will reduce the likelihood of direct human exposure to contaminants at the source.

6 Sampling Analysis and Quality Plans

The following sampling plans detail sampling exercises in accordance the Monitoring Program detailed within Section 5 of the SHRSC WCMP.

- Section 5.4 of the WCMP provides frequency of scheduled sampling activities;
- Section 5.4 of the WCMP provides the concentrations of analytes used in the assessment;
- Section 5.3 of the WCMP provides information on constraints and limitations for sampling surface waters off range; and
- Section 5.5 WCMP provides adopted assessment criteria and derivation method for EILs.

During the sampling activity any variations from the SAQP should be recorded for reference in the future annual review.

6.1 SAQP for the 800m Range

Table 2 provides the Sampling Rationale Matrix for the 800m range.

TABLE 2 – Sampling Rationale Matrix (800m Range)			
Sample Location	Sample type	Context (in landscape) of Sample location	Rationale for selection
Bullet Catcher	Gravel (per Soil)	Primary Impact Zone	Confirm levels in area of expected contamination
Stop butt above bullet catcher	Soil	Face of stop- butt behind targets – impact area and adjacent to impact area	Confirm levels in area of expected contamination
Rear of stop butt	Soil	Possible shot fall area	Confirm no contamination
Bench in front of stop butt	Soil	Down gradient of stop butt impact area	Confirm levels in expected area of contamination. Identify contamination
Gallery	N/A	Shot fall area	Concrete area – record of cleaning to be made. Record visual inspection
Target Mound/Mantlet and associated drainage	Soil	Mound in front of galley – potential impact area	Confirm levels in expected area of contamination. Identify migration of contamination
Area in front of Mantlet	Soil	Outside drainage to impact areas	Identify migration of contamination
Over storeroom – west of gallery	Soil	Outside drainage to impact areas	Identify migration of contamination
New culvert East of Stopbutt	Soil	Down gradient of stop butt impact area	Confirm levels in expected area of contamination. Confirm/characterise migration of contamination
Mulched area behind stop butt	Soil	Down gradient of impact area– water quality area for stop butt	Confirm levels in expected area of contamination. Confirm migration of contamination

Outlet from mulched area	Soil, water, sediment	Discharge point for surface water	Assess for contamination from local catchment
Basin: East of 800m range	Surface, water sediment	Surface water from road and part range areas	Assess for contamination from local catchment
Pits – Lime treatment process	Water, Sediment if present	Possible water and sediment from primary impact area stop butt and surrounds	Monitor function of lime treatment process. Assess for failure of control and movement of sediment

Tables 3A -C provide the suite of analytes, planned location and numbers of samples at the 800m range as prepared for the SAQP.

Metals of concern included in the analysis suite are those to be common in the composition of bullets.

Depth of samples is generally 100mm as this reflects the expectation of shot fall lying on or near to the surface and also the possible migration of contaminants primary via surface run off.

Additional samples may be taken in other locations due to site conditions and observations made at the time of sampling.

Analytes/Suite	Locations	Number (SAQP)
PAH	Stop butt/bullet catcher (impact area behind targets)	2
Cadmium	Stop butt non-shot area – between bullet catchers	2
Arsenic	Stop butt directly under bullet catcher	2
Chromium	Gallery area- concrete	NIL-Visual only
Mercury	Bench at front of butt/foot of stop butt	only
Nickel	Target mound/mantlet	3
Tin	In front of target mound/mantlet and associated drainage	3
pH		3
Lead	Stop butt –rear	1
Copper	West of Gallery (grassed area over store room)	1
Zinc	Below outlet of culvert from stop butt drainage	2
Antimony	Exit channel from sump to offsite- to flow line over escarpment	2
Iron		2
CeC		
Clay Content	Duplicate samples	
TCLP	Triplicate samples	2
(for samples with elevated results only)		2
	Total	25

Analytes/Suite	Locations	Number
Nickel	Basin adjacent to 800m range	1
Arsenic	Reservoir in lime treatment unit	1
Chromium	Channel at rear of 800m range (If available)	1

Total Phosphorus (TP) Total Nitrogen (TN) Ammonia (NH3) Dissolved Oxygen (DO) pH 1 Lead Copper Zinc Antimony Phosphate	Pit within Lime treatment process (if accessible and water present)	1
	Total	4

TABLE 3C: SEDIMENT (800m Range)			
Analytes/Suite	Locations	Number	
PAH	Basin adjacent to 800m range	1	
Cadmium	Pit within Lime treatment process (if accessible and sediment present)	1	
Arsenic			
Chromium			
Mercury			
Nickel			
Tin			
Clay Content			
pH			
Lead			
Copper			
Zinc			
Antimony			
Iron			
CeC			
TCLP (for samples with elevated results only)			
		Total	2

6.2 SAQP for the 50m and 500m Range

Table 4 below gives the Sampling Rationale Matrix for the 50 and 500m Ranges.

TABLE 4: SAMPLING RATIONALE MATRIX: 50M & 500M RANGES			
Sample Location	Sample Type	Context (in landscape) of Sample location	Rationale for selection
On range (500m)	Soil	Main body of range / fairway/shot zone	Identify contamination – confirm no migration of contamination
On range (50m)	Soil or Gravel	Main body of range	Identify contamination – confirm no migration of contamination
Face of stop butt / bullet catcher	Gravel	Impact area of range	Confirm concentrations of expected contamination
Face of stop butt above bullet catcher	Soil	Potential impact area of range	Confirm concentrations of expected contamination
Area immediately in front of toe of stop butt associated drainage	Soil	Outside drainage to impact area	Confirm no migration of contamination
Basins/basins	Water, sediment	Basins receive water from range areas	Confirm no migration of contamination Confirm water quality parameters
Rear of stop butt	Soil	Possible shot fall area	Confirm no contamination
Creek water off range (where available from Ephemeral creeks following rainfall or from natural pools)	Water, sediment	Separate from range run off	Confirm no migration of contamination. Confirm water quality parameters
Pits within the Lime treatment process (Note Lime and directional pits do not retain water)	Water, Sediment if present	Possible water and sediment from primary impact area stop butt and surrounds	Monitor function of lime treatment process. Assess for failure of control and movement of sediment

Tables 5A -C provide the suite of analytes, planned location and numbers of samples at the 50m and 500m ranges as prepared for the SAQP.

Metals of concern included in the analysis suite are those to be common in the composition of bullets.

Depth of samples is generally 100mm as this reflects the expectation of shot fall lying on or near to the surface and also the possible migration of contaminants primary via surface run off.

Additional samples may be taken in other locations due to site conditions and observations made at the time of sampling.

TABLE 5A: SOILS				
Analytes/Suite	Range	Locations	Number	
PAH	500	On range – 1 from each target bay	7	
Cadmium		- plus random over all bays (max 2 per bay)	3	
Arsenic			5	
Chromium		Off range / bush land	3	
Mercury		Face of stop main stop butt	6	
Nickel		-plus 1 from each intermediate mound	3	
Tin				
pH		Within 10m in-front of toe of main	6	
Lead		Stop-butt and associated drainage		
Copper		-plus 1 from in front of each		
Zinc		intermediate mound		
Antimony		50	On range – gravel or soil range floor	3
Iron			Off range / bushland	3
CEC	Face of stop butt – bullet catcher		3	
Clay Content	Face of stop butt – from above		2	
TCLP	bullet catcher		1	
(for samples with elevated results only)	Soil material below invert of bullet catcher		3	
	Within 10m in-front of toe of Stop-butt and associated drainage			
	50m/500m range	Duplicate sample	1	
		Triplicate sample	1	
	Total		50	

TABLE 5B: WATER		
Analytes/Suite	Locations	Number
Nickel	Basin at car park (Basin 4)	1
Arsenic	50m (Basin 5)	1
Chromium	500m East (Basin 3)	1
Total	500m West (Basin 2)	1
Phosphorus (TP)	200m (Basin 1)	1
Total Nitrogen (TN)	Creek waters off range (where available from Ephemeral creeks following rainfall or from natural pools)	2
Ammonia (NH3)	Pits in Lime treatment process (if accessible/ present)	8
Dissolved Oxygen (DO)	Duplicate sample	1
pH 1	Triplicate sample	1
Lead		
Copper		
Zinc		
Antimony		
Phosphate		
Turbidity		
	Total	18

TABLE 5C: SEDIMENT		
Analytes/Suite	Locations	Number
PAH	Basin at car park (Basin 4)	1
Cadmium	50m (Basin 5)	1
Arsenic	500m East (Basin 3)	1
Chromium	500m West (Basin 2)	1
Mercury		
Nickel	200m (Basin 1)	1
Tin	Creek waters off range (where available from Ephemeral creeks following rainfall or from natural pools)	2
Clay Content		
pH		
Lead	Pits within Lime treatment process (if present)	8
Copper		
Zinc		
Antimony		
Iron		
CEC		
TCLP (for samples with elevated)		
	Total	15

6.3 Visual Inspections

Section 5.4 of the SHRSC WCMP presents the items and frequency for visual inspections. These inspections are summarised following.

6.3.1 Water quality structures and surrounds

Inspect water quality basins for;

- evidence of scour from flows at inlet or outlet
- evidence of scour or failure at inside batters of structures
- evidence of scour, instability or failure of external batters of structure

6.3.2 Engineering controls – earthworks

Inspect Berms, drains channels, stock butts, access tracks and culverts for;

- evidence of scour from flows at inlet or outlet of culverts and channels or at invert of channels and drains.
- evidence of instability or erosion of track surfaces and associated drainage.
- evidence of scour, instability or failure of batters or formation of stopbutts.

6.3.3 Engineering controls – lime treatment process

Inspect accessible subsurface elements of lime treatment process / Engineering controls for;

- Evidence of fragments of bullets and other extraneous materials within pits or chambers of the treatment control.
- Evidence of sediment washed into pits or chambers of the treatment control.

6.3.4 Safety and signage

Inspect site safety and signage including fencing around sediment basins and drainage measures for;

- Visibility of signage
- Location per that in SHRSC OEMP
- Condition

6.3.5 Shot loss

Inspect Range perimeter, especially 800m and 500m ranges for;

- Evidence of loss and/or damage from stray projectiles

6.3.6 Vegetation health

Inspect vegetation health of range floor and revegetated areas for;

- Percentage of ground cover -equivalent to C factor of 0.1 or lower (see WCMP)
- and vigour

6.4 Methodology

6.4.1 Soil sampling methodology

1. Soil Samples are to be collected in ~250ml glass sample jars provided by the Analytical Laboratory. Jars are to be labelled with;
 - Project title
 - Sample ID Number
 - Depth of Sample
 - Date of Sample
 - Identifier of Officer taking Sample
2. Samples will then be packed in a cooler with ice packs prior to being transported to the laboratory and tracked under chain of custody documentation.
3. Soil samples to be collected using a shallow auger or similar within the top 100mm of the soil surface where bullet or fragments was expected to be present (unless indicated otherwise).
4. Where soil material is too hard or soft for the auger, material was collected using a hand mattock/tool.
5. Where soils are observed to be excessively friable or where rocks/vegetation were present repeated samples are to be collected adjacent to each other to obtain an adequate sample volume.
6. Soil samples below 100mm if required are to be collected using a hand auger with extensions.
7. Vegetation/grass and rocks/gravel are to be screened from the samples collected.
8. Where shot fragments or projectiles are found in the sample these are to be removed and their presence recorded so that pure lead shot is not included in the sample submitted for analysis.
9. Between each sample collection the auger or hand tool is to be decontaminated by removing excess material from the face of the tool and washed down with distilled water.
10. Nitrile gloves are to be worn during sample collections and changed between locations to avoid cross contamination from the samplers hands.

6.4.2 Sediment sampling methodology

1. Sediment Samples are to be collected in ~250ml glass sample jars provided by the Analytical Laboratory. Jars are to be labelled with;
 - Project title
 - Sample ID Number
 - Depth of Sample
 - Date of Sample
 - Identifier of Officer taking Sample

2. Samples are then then packed in a cooler with ice packs prior to being transported to the laboratory and tracked under chain of custody documentation.
3. Sediment samples are to be collected within identified contaminant flow paths from ground level alluvium in surface water channels or from settled sediments at the sides of the water quality basins using a hand mattock or similar suitable collection tool.
4. The collection tool is to be decontaminated using distilled water prior to collection.
5. Nitrile gloves are to be worn during sample collections and changed between locations to avoid cross contamination from the samplers hands.

6.4.3 Water sampling methodology

1. Water samples are to be collected in a laboratory prepared and provided collection bottle. Bottles are to be labelled with;
 - Project title
 - Sample ID Number
 - Depth of Sample
 - Date of Sample
2. Samples will be collected from water quality basins using a sample bailer/pre-washed bottle attached to a sampling pole so samples could be collected from greater than 1.5m from the edge of the basin.
3. Samples collected from natural streams or pools within streams are to be collected from the middle of streams / pools.
4. Prior to collecting a sample the sample bailer bottle is rinsed with distilled water. And the rinsate is discarded well away from sample location.
5. Water samples were transferred to the collection bottles provided by the laboratory. Samples were then packed in a cooler with ice packs prior to being transported to the laboratory and tracked under chain of custody documentation and within the confirmed holding times for the various analytes.

Field Sampling

Field sampling of Soil pH or Water (pH or Turbidity) are to undertaken in accordance with the instrument guidelines.

Field instruments are to be confirmed as calibrated per instrument guidelines and before every sampling exercise undertaken as part of the Monitoring Program within the SHRSC WCMP.

6.5 Laboratory QA QC

The following information has been provided by the laboratory selected for the analysis (Envirolab Services Chatswood NSW.)

NATA Accreditation

Envirolab is accredited by NATA to ISO 17025 under corporate accreditation number is 2901.

Quality Assurance

Envirolab is NATA accredited to AS ISO/IEC 17025. This includes all aspects of the analytical process including sample preservation, sample registration, methodology, instrument calibration and maintenance, data records, calculations and reporting of results.

The laboratory operates under a definitive plan which specifies the measures used to produce data of a known precision and bias. The quality assurance plan includes implementation of Quality Control and Quality Assessment Procedures.

Quality Control is a set of measures within a sample analysis methodology to assure that the process is in control.

Quality Control measures included:

- *Certification of operator competence*
- *Recovery of known additions*
- *Analysis of externally supplied standards*
- *Analysis of reagent blanks*
- *Calibration with standards*
- *Analysis of duplicates*
- *Control charts*

Quality Assessment is the procedure for determining the quality of laboratory measurements by use of data from internal and external quality control measures.

Quality Assessment measures included:

- *Laboratory inter-comparison trials*
- *Performance evaluation samples*
- *Performance audits*

Envirolab met or exceeded NEPM (2013) guidelines for QC for this assessment.

The Quality Control guidelines for this assessment were:

- *Duplicate: every 10 samples or per batch if <10*
- *Matrix Spike: every 20 samples or per batch if <20*
- *LCS: every 20 samples or per batch if <20*
- *Blank: every 20 samples or per batch if <20*

6.6 Laboratory Methods

Tables 6A and 6B below summarise the laboratory methods and NATA accreditation for each of the analytes for Soil/Sediment and Waters. Details within this table have been taken from the laboratory's capability statement.

Table 6A :Soil /Sediment				
Analysis suite	Technique	Reference method	PQL mg/L	NATA
Cadmium	020 ICP-AES	NIOSH 7301	0.4	Y
Arsenic			4	
Chromium			1	
Mercury			0.1	
Nickel			1	
Tin			1	
Lead			1	
Copper			1	
Zinc			1	
Antimony			7	
Iron			1	
PAH	Org-012 subset	USEPA 8270	+ve/-ve	Y
CEC	ICP	Aust. Lab Handbook 15B3	1meq/100g	
Clay Content	Hydrometer		1%	
pH	soil/water electrode	USEPA 9045	0.1 unit	Y

Table 6B: Water				
Analysis suite	Technique	Reference method	PQL	NATA
pH	Electrode	APHA4500H+	0.1 unit	Y
Arsenic	Metals-022 ICP-MS	USEPA 200.8 USEPA 3005A (prep) USEPA 6020A	1 µg/L	Y
Chromium			1 µg/L	
Nickel			1 µg/L	
Lead			1 µg/L	
Copper			1 µg/L	
Zinc			1 µg/L	
Antimony			1 µg/L	
Phosphate			Colourmetric	
Ammonia	Paste	EPA 350.1	0.005mg/L	Y
Total Nitrogen	Colourmetric	APHA4500-Norg	0.1 mg/L	Y
Total Phosphorous	ICP-AES or Colourmetric	USEPA 200.7 or APHA 4500-P	0.05mg/L	Y
Dissolved Oxygen		Inorg-112	0.1	

7 Site Assessment Criteria

7.1 Rationale for Selection of Assessment Criteria

The following published assessment criteria have been referenced in the summary of results tables to characterise the contamination status of the site.

Comments are offered detailing why each criterion has been selected.

Section 6.1.1 presents the method for determination of EILs used for this assessment.

The data previously collected from non-operational areas of the SHRSC and surrounds has been used to determine Ambient Background Concentrations (ABC) as part of derivation of the EILs to be applied on the operational ranges.

Soil

NEPM

National Environment Protection (Assessment of Site contamination) Measure (2013) Health investigation level (HILs)

- C – Developed Open Space such as parks, playgrounds, playing fields
- D - Commercial/industrial includes premises such as shops, offices, factories and industrial sites.

The site is currently zoned as SP1: Special Activities – Shooting Range. The HIL C has been adopted as Tier 1 soil trigger values for management response. The HIL D have been presented for comparison and further discussion given that the shooting ranges are proposed to be managed and operated as a commercial facility.

NEPM

National Environment Protection (Assessment of Site contamination) Measure (2013) Ecological Investigation Levels (EILs)

Sediment

ANZECC

Water Quality Guidelines Chapter 3- Section 3.5.4 Table 3.5.1 Interim Sediment Quality Guidelines (LOW and HIGH triggers) (Australian and New Zealand Guidelines for Fresh and Marine Water Quality, Australian and New Zealand Environment and Conservation Council, 2000)

Water

ANZECC PFWS

Protection of fresh water species - 95% level of protection trigger values (Australian and New Zealand Guidelines for Fresh and Marine Water Quality, Australian and New Zealand Environment and Conservation Council, 2000) (Note that the NEPM GILs for Freshwater have been adopted from the ANZECC 2000 guidelines.)

The ANZECC PFWS was selected due to the proximity to fresh water courses and fresh groundwater

ANZECC RWCG

Recreational Water Quality Guidelines (Australian and New Zealand Guidelines for Fresh and Marine Water Quality, Australian and New Zealand Environment and Conservation Council, 2000)

NEPM

National Environment Protection (Assessment of Site contamination) Measure (2013) Ground Water Investigation Levels (GILs) for Freshwater.

GILs for Antimony (Sb), within the 2000 Australian and New Zealand Guidelines for Fresh and Marine Water Quality, Volume 2. Aquatic Ecosystems — Rationale and Background Information (Chapter 8) are not available due to insufficient data. As such a Low Reliability Trigger Value has been adopted.

7.1.1 Derivation of Ecological Investigation Levels (EILs)

This section presents the NEPM 1999 (amended 2013) method adopted by ErSed to derive the Ecological Investigation Levels (EILs) for this assessment.

Ecological Investigation Levels EILs (EILs) have been derived by summing the Ambient Background Concentration (ABC) and the Added Concentration Limit for the contaminants of concern i.e.

$$\text{EIL} = \text{ABC} + \text{ACL}$$

Derivation of ABC

Samples were collected from non-operational areas of the SHRSC and the heavy metal analytical results were used as a background sample data set. Data from samples collected from surface soils taken from drainage areas (sediments) was also used within the set.

Where sample results were below the limit of laboratory detection (i.e. <LOR) these were adjusted to the detection limit. The geometric mean of the data was used as the ABC to derive the EIL.

Derivation of ACL

Ambient Concentration Limits (ACLs) for metal analytes have been referenced from Tables 1(B) Schedule B1 (NEPM 2013).

Where required the geometric mean of pH and CEC have been used to calculate the ACL. The geometric mean for the clay content from samples taken from the 800m range has been used as a conservative value.

For the calculations of the EILs for lead (Pb) and copper the consultant has assumed that the criteria for public open space is the most relevant to the current site use.

7.1.2 Referenced NEPM 1999 (2013) Tier 1 Health Investigation Levels (HILs)

Published human health investigation criteria (HILs) have been sourced from table 1A Schedule B1 NEPM 1999 (Amended 2013).

As the site is currently zoned as SP1: Special Activities – Shooting Range, the HILs C – Recreational criteria will be applied.

Part B: Monitoring Program Implementation and Report

8 Monitoring Program – Implementation

Table 7 below summaries the required frequency operational monitoring detailed in Section 5.4 of the WCMP

Table 7: Annual Operational Monitoring Program

What to be monitored	Frequency
Soils - Complete (Laboratory)	Annually
- pH (Laboratory)	Six monthly
- pH (Field with laboratory confirmation at 10% of samples)	Quarterly
Sediments - Complete (Laboratory)	Annually
- pH (Laboratory)	Quarterly
- pH (Field with laboratory confirmation at 10% of samples)	Six monthly
Surface Waters - Complete (Laboratory)	Six monthly
Visual - Basins - Engineering controls - Gallery (800m Range) - Lime treatment process - Safety and signage	Annually
- Range perimeter - Vegetation health	Six monthly

Table 8 below presents the annual monitoring program prepared to meet requirements detailed within section 5.4 the WCMP.

Table 8: Monitoring Program Schedule

Quarter	Activities
1	Field Sampling – pH in Primary and Secondary Impact Areas <ul style="list-style-type: none"> • Soils • Sediments Six Monthly Visual Inspections <ul style="list-style-type: none"> • WQ Basins • Engineering Controls • Lime Treatment Process • Safety and Signage • Vegetation Health Variation: <ul style="list-style-type: none"> • Replace laboratory pH analysis for Field Sampling pf pH. (Q1 & Q2) • Include pH for Surface waters in Q1 and Q3.
2	Six Monthly Monitoring - pH in Primary and Secondary Impact Areas <ul style="list-style-type: none"> • Soils • Sediments Six Monthly Monitoring <ul style="list-style-type: none"> • Surface Waters
3	Field Sampling – pH in Primary and Secondary Impact Areas

	<ul style="list-style-type: none"> • Soils • Sediments <p>Six Monthly Visual Inspections</p> <ul style="list-style-type: none"> • WQ Basins • Engineering Controls • Lime Treatment Process • Safety and Signage • Vegetation Health <p>Annual Visual Inspection of Range perimeter for shot loss.</p> <p>Variation:</p> <ul style="list-style-type: none"> • Replace laboratory pH analysis for Field Sampling pf pH. (Q1 & Q2) • Include pH for Surface waters in Q1 and Q3.
4	<p>Annual Monitoring</p> <ul style="list-style-type: none"> • Soil • Surface Waters • Sediments

Summaries of the Q4 sampling event are provided in the following sections.

Laboratory results for Q4 monitoring events are provided within Appendixes for each separate quarter;

- **Appendix 1: Laboratory Results**

9 Monitoring Program – Quarter 4

A samplings exercise was undertaken **20 JUNE 23** in accordance with Section 8.

A summary of the sampling event is given below.

Variation this sampling event:

Additional items within the sampling exercise are indicated within table 9 below.

Summary of sampling event

Table 9: Quarter 4 Sampling Event

Aspect	See Report Section
<p>Annual Monitoring</p> <ul style="list-style-type: none"> • Soil • Surface Waters • Sediments <p>Additional</p> <p>Following recommendations from previous sampling;</p> <ul style="list-style-type: none"> • Water Lab pH to be included in every sampling exercise • Ammonia as N - If water is present within the drainage line at rear of 800m stop butt 	9.1

9.1 Sampling (pH) Soil, Sediments and Surface Waters

The results from the QTR4 sampling exercise are provided for each range following within Appendix 1.

Results outside or the target criteria are discussed at Section 9.3.

9.2 Six Monthly Visual Inspections

Not required this Quarter.

Six Monthly Visual inspections are undertaken and Reported Q1 and Q3.

9.3 Discussion of results

Full results from the Annual monitoring for soils, sediments and surface waters is provided within Appendix 1.

Results outside the target criteria for all analytes are indicated in **RED**.

Results outside the target criteria are discussed at following.

9.3.1 Discussion of Results – pH Soils, Sediments and Surface Waters 50m range

TABLE 10: SOIL & SEDIMENT & SURFACE WATERS RESULTS 50m		DATE: 20 JUNE 23
Sample ID	Sample Location	pH Units
RANGE OF VALUES – SOILS AND SEDIMENTS		6.5-8.5
105	Bushland - South	5.6
106	Bushland - West	4.8
107	Bushland - North	5.8
	The above samples returned pH values lower than the target range of 6.5-8.5 These samples are from a bushland area where a lower pH is to be expected No action is recommended	
109	Bullet catcher -4	9
	The above sample returned a pH value over the target range of 6.5-8.5. The material within the bullet catcher consists of blue metal/basalt which can return a wide range of values based on previous environmental conditions. Other similar samples at the range returned values within the target range. No action recommended.	

112	Above Bullet Catcher 5- DUPLICATE	8.7
	<p>The above sample returned a value over the target range of 6.5-8.5.</p> <p>The formation above bullet catcher comprised of stabilised subgrade material and has returned a such values in the past. It is not in a primary shot fall area.</p> <p>No action recommended.</p>	
RANGE OF VALUES - WATER		6.5-8.5
NIL		

9.3.2 Discussion of Results – pH Soils, Sediments and Surface Water 500m range

Table 11: Soils Sediment and Surface Waters 500m range

TABLE 11: SOIL & SEDIMENT RESULTS 500m		DATE: 20 JUNE 23
Sample ID	Sample Location	pH
RANGE OF VALUES - SOIL		6.5-8.5
201	Bushland 1 - South	5.5
202	Bushland 2-West 1	5.6
203	Bushland 3- West 2	5.6
204	Bushland 4 -East	5.4
204	DUPLICATE	-
205	Bushland 5- North	5.4
	<p>The above samples returned pH values lower than the target range of 6.5-8.5 These samples are from a bushland area where a lower pH is to be expected</p> <p>No action is recommended</p>	
215	Range floor 200-285m	6.2
217	Range floor 350-500m	6.1
217	DUPLICATE	6.2
218	Ad. Range Floor 6	5.9
226	Int Mound 6- 385m	5.6
236	10m in front - Mound 6	6.4
238	10m- butt - Central	6.3
239	10m - butt - East	6
239	DUPLICATE	6
	<p>The above samples returned pH values just below the target pH range of 6.5-8.5</p> <p>This is a re-occurring result for the range floor and associated with the natural soil material of the range floor. This issue is managed by regular application of Agricultural lime</p> <p>The receiving waters for the 500m catchment are within the target pH range</p> <p>Regular application of agricultural lime should be continued.</p>	
258	Sediment below Basin 3 (500 East)	6.4

TABLE 11: SOIL & SEDIMENT RESULTS 500m		DATE: 20 JUNE 23
Sample ID	Sample Location	pH
RANGE OF VALUES - SOIL		6.5-8.5
	The above sample is from a basin with bushland area and catchments where a lower pH is to be expected. No action is recommended.	
258	Sediment - Basin 1	6.2
	The above sample are from a basin with bushland areas and catchments where a lower pH is to be expected. No action is recommended.	
265	Sed Basin 4 – car park	6.2
	The above sample is from a basin with bushland areas and catchments where a lower pH is to be expected. The catchment to basin 4 is a car park and access area. It does receive and waters from an active shooting range. No action is recommended.	
RANGE OF VALUES – WATER		6.5-8.5
NIL		

9.3.3 Discussion of Results – pH Soils, Sediments and Surface Waters 800m range

Table 12: Soils Sediment and Surface Waters 800m range

TABLE 12: SOIL & SEDIMENT RESULTS 800m		DATE: 20 JUNE 23
Sample ID	Sample Location	pH
RANGE OF VALUES - SOIL		6.5-8.5
301	Bullet catcher 2	9.2
302	Bullet catcher 4	9.1
	The above samples returned a pH value over the target range of 6.5-8.5. The material within the bullet catcher consists of blue metal/basalt which can return a wide range of values based on previous environmental conditions. Other similar samples at the range returned values within the target range. No action recommended.	
322	Basin 7 (off 800)- Duplicate	6.4
	The above sample is from a basin with bushland areas and catchments where a lower pH is to be expected. The catchment to basin 4 is the unsealed access track. It does receive and waters from an active shooting range. No action is recommended.	

TABLE 12: SOIL & SEDIMENT RESULTS 800m		DATE: 20 JUNE 23
RANGE OF VALUES – WATER		6.5-8.5
331	Basin 7 – off 800m	6.3
<p>The above sample is from a basin with bushland areas and catchments where a lower pH is to be expected.</p> <p>The catchment to basin 4 is the unsealed access track. It does receive and waters from an active shooting range.</p> <p>No action is recommended.</p>		

9.3.4 Discussion of Results – Soil and Sediments – Other Criteria

TABLE 13: SOILS - EXCEEDANCES OTHER CRITERIA		DATE: 20 JUNE 23	
Sample ID	Location	Analyte	Value (mg/kg)
50m Range			
109	Bullet catcher -4	Copper	1300
	<ul style="list-style-type: none"> Sample 109 above returned a value for copper over the Ecological Investigation Level (EIL) criteria but under the HIL (C &D) criteria. The samples above returned values for Lead over the Ecological Investigation Level (EIL) criteria and the HIL (C &D) criteria. This samples are taken from within the primary impact zone or shot fall areas and as such expected to reflect contamination from bullets. <p>No action is recommended.</p>	Lead	1700
		Zinc	5800
111		Above Bullet Catcher 2	Lead
111	Duplicate	Lead	1600
	<ul style="list-style-type: none"> Sample numbers 111 returned values for Lead over the EIL from the WCMP and HIL (C) & (D) HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. This sample is taken from immediately above the primary impact zone and as such expected to reflect contamination from bullets. <p>No action is recommended.</p>		
112	Above Bullet Catcher 5	Lead	1300
	<ul style="list-style-type: none"> Sample numbers 112 returned a value for Lead over the EIL from the WCMP and HIL (C) but under the criteria for HIL (D). HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. This sample is taken from immediately above the primary impact zone and as such expected to reflect contamination from bullets. 		
500m Range			
222	Int Mound 2- 100m	Lead	940
223	Int Mound 3- 200m	Lead	3800

TABLE 13: SOILS - EXCEEDANCES OTHER CRITERIA			DATE: 20 JUNE 23	
Sample ID	Location	Analyte	Value (mg/kg)	
50m Range				
226	Int Mound 6- 385m	Lead	940	
236	10m in front - Mound 6	Lead	4000	
	<ul style="list-style-type: none"> • Samples above returned values for Lead over HIL (C) but under the EIL from the WCMP and HIL (C) & (D) • Samples 223 and 236 returned lead levels also over the EIL from the WCMP and HIL (C) & (D) • HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. • This sample is taken from the primary impact zone and as such expected to reflect contamination from bullets. <p>Observations on site indicate that the 500m range is being used such that bullet strike is occurring within the first portions of the 500m range. As such these may also be considered primary shot fall areas.</p> <p>No action is recommended.</p>			
236	10m in front - Mound 6	Copper	2500	
	<ul style="list-style-type: none"> • The above sample returned a value for Copper over HIL (C) but under the EIL from the WCMP and HIL (C) & (D) • HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. • This sample is taken from the primary impact zone and as such expected to reflect contamination from bullets. <p>Observations on site indicate that the 500m range is being used such that bullet strike is occurring within the first portions of the 500m range. As such these may also be considered primary shot fall areas.</p> <p>No action is recommended.</p>			
237	10m - butt - West	Lead	4300	
238	10m- butt - Central	Lead	4300	
	<ul style="list-style-type: none"> • The above samples above returned values for Lead over the EIL from the WCMP and HIL (C) & (D) • HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. • This sample is taken from immediately above the primary impact zone and as such expected to reflect contamination from bullets. <p>No action is recommended.</p>			
800m Range				
301	Bullet catcher 2	Lead	3300	
302	Bullet catcher 4	Lead	5900	
306	Butt under BC 6	Lead	690	
	<ul style="list-style-type: none"> • The above samples above returned values for Lead over the EIL from the WCMP and HIL (C) & (D) 			

TABLE 13: SOILS - EXCEEDANCES OTHER CRITERIA		DATE: 20 JUNE 23	
Sample ID	Location	Analyte	Value (mg/kg)
50m Range			
	<ul style="list-style-type: none"> HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. <p>This sample is taken from immediately the primary impact zone and as such expected to reflect contamination from bullets.</p> <p>No Action is Recommended.</p>		
303	Above bullet Catcher 3	Lead	6100
		Copper	190
303	DUPLICATE	Lead	2800
		Copper	7800
		Zinc	330
	<p>The above samples above returned values for</p> <ul style="list-style-type: none"> Lead over the EIL from the WCMP and HIL (C) & (D) Copper over the EIL from the WCMP but under the HIL (C) & (D) Zinc over the EIL from the WCMP but under the HIL (C) & (D) HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. <p>This sample is taken from immediately above the primary impact zone and as such expected to reflect contamination from bullets.</p> <p>No Action is Recommended.</p>		
311	10m Mantlet Centre	Lead	670
	<p>The above sample above returned values for Lead over the EIL from the WCMP and HIL (C) & (D)</p> <ul style="list-style-type: none"> HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. <p>This sample is taken from an area in front of the target area and should be be within primary impact zone and as such is expected to reflect contamination from bullets.</p> <p>No Action is Recommended. This area will be reviewed in subsequent monitoring events.</p>		
313	Bench West	Lead	1200
		Copper	140
314	Bench Central	Lead	2200
		Copper	410
314	DUPLICATE	Lead	1900
		Copper	1100
315	Bench East	Lead	3000
		Copper	15000
		Zinc	530

TABLE 13: SOILS - EXCEEDANCES OTHER CRITERIA		DATE: 20 JUNE 23	
Sample ID	Location	Analyte	Value (mg/kg)
50m Range			
	<p>The above samples above returned values for</p> <ul style="list-style-type: none"> Lead over the EIL from the WCMP and HIL (C) & in some cases also (D) Copper over the EIL from the WCMP but under the HIL (C) & (D) Zinc over the EIL from the WCMP but under the HIL (C) & (D) – sample 315 only HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises. <p>This sample is taken from immediately below the primary impact zone and as such expected to reflect contamination from bullets.</p> <p>No Action is Recommended.</p>		
323	Sediment – gallery	Lead	2400
		Copper	200
		Zinc	2300
	<p>The above samples above returned values for</p> <ul style="list-style-type: none"> Lead over the EIL from the WCMP and HIL (C) & (D) Copper over the EIL from the WCMP but under the HIL (C) & (D) Zinc over the EIL from the WCMP and HIL (C) & (D) <p>HIL (C) relates to Open spaces and recreational areas. HIL(D) is for commercial/industrial premises.</p> <p>This sample is taken from sediment accumulated from various catchments within the primary impact area.</p> <p>As this sediment is accumulated it is removed and disposed of as waste.</p> <p>No Action is Recommended.</p>		

9.3.5 Discussion of Results – Surface Waters – Other Criteria

TABLE 14: WATERS - EXCEEDANCES OTHER CRITERIA		DATE: 20 JUNE 23	
Sample ID	Location	Analyte	Value
NIL			

10 Recommendations and Annual Summary

10.1 Recommendations and Management Actions

The following recommendations are made subsequent to this monitoring event;

As part of the Annual Reporting, recommendations from Q1-3 2024 are also provided. A summary of recommended changes to the SAQP / Monitoring Program is also provided from all Quarters.

10.1.1 Management Actions Q4

The following management actions are presented summarised from section 9.3;

1. Regular application of agricultural lime should be continued

10.1.2 Management Actions Q1-3

1. Investigate/schedule works to improve/ reinstate inlet controls at Basin 1 and Basin 3.
2. Include clearing of sediment from drainage and culverts within the road network to the 50m and 500m ranges as part of regular maintenance.
3. Investigate works to re shape top of stop butt mounds at the 50 and 500m ranges
4. Investigate works to improve stabilisation/vegetation rear of the stop butt mounds at the 50 and 500m ranges and associated drainage
5. Investigate works to improve check measures (as required) at the swale drains at the Eastern side of the 500m range and South Eastern corner of the 500m range.
6. Investigate works to maintain / improve drainage outlet at the southern corner at rear of 500m range.
7. Maintain scheduled regular treatment of the 500m range floor with Agricultural Lime.
2. Additional controls should be considered for the drainage channel at the rear of the 800m stop butt. It is recommended that a series of shaped limestone check structures should be formed within the drainage swale to detain water and force drainage from the mulched area at the rear of the butt to pass through the limestone.
3. Schedule weed control works to remove woody plants from stop butt areas of the 50 and 500m ranges and from gabion outlets (especially basins 1,3 and 5).

10.1.3 Follow up Monitoring Recommendations

The Results returned at the rear of the 800m range stop butt suggest that the further sampling to identify the extent of a potential hotspot at the rear of the stop but which does not drain to the sealed "lime " treatment unit.

This will be proposed to be undertaken associated with the next quarter sampling exercise.

10.1.4 Changes to Monitoring Program

No specific changes to scheduled monitoring/s program are recommended.

Note additional items this quarter are to be continued.

- Field sampling of Soil pH may be replaced with laboratory pH as this provides equal or better observations.
- Water Lab pH to be included in every sampling exercise
- Ammonia as N - If water is present within the drainage line at rear of 800m stop butt

11 References

Southern Highlands Regional Shooting Complex, Water Cycle Management Plan (ErSed Sept 2018)

National Environment Protection (Assessment of Site Contamination) Measure (NEPM), National Environment Protection Council (2013).

National Environment Protection (Assessment of Site Contamination) Measure (NEPM), Schedule B1 Guideline on Investigation Levels for Soil and Groundwater, National Environment Protection Council (2011).

Australian and New Zealand Guidelines for Fresh and Marine Water Quality, Australian and New Zealand Environment and Conservation Council (October 2000).

Guidelines for Consultants Reporting on Contaminated Sites, NSW Office of Environment and Heritage (2011).

Contaminated Sites: Guidelines for the NSW Site Auditor Scheme (2nd edition), NSW Department of Environment and Conservation (2006).

Best Management Practices for Lead at Outdoor Shooting Ranges, United States Environmental Protection Agency (2005).

Southern Highlands Regional Shooting Complex Civil Works Plans Drawings C-SC-202-253 (Arcadis Australia Pacific Pty Limited, 2015)

12 Appendices

Appendix 1 – Results

TABLE 22	SOIL AND SEDIMENT RESULTS - 50M
TABLE 23	SOIL AND SEDIMENT RESULTS - 500M
TABLE 24	SOIL AND SEDIMENT RESULTS - 800M
TABLE 25	SURFACE WATERS (50M, 500M & 800M)

TABLE 15 SOIL & SEDIMENT RESULTS 50m															DATE: 20 JUNE 2023				
Sample ID	Sample Location	PAH-Total	PAH-B(a) PTEQ	PAH-B(a)P	Arsenic	Cadmium	Chromium	Copper	Lead	Mercury	Nickel	Zinc	Tin	Antimony	Iron	CEC	pH	Clay in Soil <2µm	
	Units	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	meq/100g	pH Units	% W/W	
EIL from WCMP				(ESL) 0.7	100	-	414	132	1113	-	34	190	OBS ONLY	-	OBS ONLY				OBS ONLY
HIL (C)		300	3	-	300	90	300	17000	600	13	1200	30000		252					
HIL (D)			-	-	3000	900	3600	240000	1500	180	6000	400000							
RANGE OF VALUES																	6.5-8.5		
Practical Quantitation Limit or Limit of Reporting (PQL)		0.05			4	0.4	1	1	1	0.1	1	1	1	7	10	1			
101	Range 1 – Floor	<0.05	<0.5	<0.05	<4	<0.4	15	16	12	<0.1	7	37	[NT]	[NT]	[NT]	[NT]	8.5	[NT]	
101	DUPLICATE	<0.05	<0.5	<0.05	<4	<0.4	16	15	10	<0.1	7	33	[NT]	[NT]	[NT]	[NT]	8.5	[NT]	
102	Range Floor 2	<0.05	<0.5	<0.05	<4	<0.4	2	1	5	<0.1	<1	9	[NT]	[NT]	[NT]	[NT]	7.7	[NT]	
103	Range Floor 4	<0.05	<0.5	<0.05	<4	<0.4	3	<1	5	<0.1	<1	5	[NT]	[NT]	[NT]	[NT]	7.3	[NT]	
104	Range Floor 5	<0.05	<0.5	<0.05	<4	<0.4	7	2	59	<0.1	2	12	[NT]	[NT]	[NT]	[NT]	7.3	[NT]	
105	Bushland - South	<0.05	<0.5	<0.05	<4	<0.4	11	<1	31	<0.1	1	5	[NT]	[NT]	[NT]	[NT]	5.6	[NT]	
106	Bushland - West	<0.05	<0.5	<0.05	<4	<0.4	9	1	11	<0.1	1	6	[NT]	[NT]	[NT]	[NT]	4.8	[NT]	
107	Bushland - North	<0.05	<0.5	<0.05	<4	<0.4	17	1	11	<0.1	3	6	[NT]	[NT]	[NT]	[NT]	5.8	[NT]	
108	Bullet catcher -3	<0.05	<0.5	<0.05	<4	<0.4	1	2	340	<0.1	<1	5	[NT]	[NT]	[NT]	[NT]	8	[NT]	
109	Bullet catcher -4	<0.05	<0.5	<0.05	7	<0.4	10	13000	17000	<0.1	3	5800	[NT]	[NT]	[NT]	[NT]	9	[NT]	
110	BC or Mantlet - BAY	<0.05	<0.5	<0.05	<4	<0.4	5	8	140	<0.1	2	15	[NT]	[NT]	[NT]	[NT]	7.7	[NT]	
111	Above Bullet Catcher 2	<0.05	<0.5	<0.05	9	<0.4	14	110	2100	<0.1	3	33	[NT]	[NT]	[NT]	[NT]	8.3	[NT]	
111	DUPLICATE	<0.05	<0.5	<0.05	<4	<0.4	7	80	1600	<0.1	3	27	[NT]	[NT]	[NT]	[NT]		[NT]	
112	Above Bullet Catcher 5	<0.05	<0.5	<0.05	5	<0.4	7	6	1300	<0.1	2	14	[NT]	[NT]	[NT]	[NT]	8.5	[NT]	

TABLE 15 SOIL & SEDIMENT RESULTS 50m															DATE: 20 JUNE 2023				
Sample ID	Sample Location	PAH-Total	PAH-B(a) PTEQ	PAH-B(a)P	Arsenic	Cadmium	Chromium	Copper	Lead	Mercury	Nickel	Zinc	Tin	Antimony	Iron	CEC	pH	Clay in Soil <2µm	
	Units	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	meq/100g	pH Units	% W/W	
EIL from WCMP				(ESL) 0.7	100	-	414	132	1113	-	34	190	OBS ONLY	-	OBS ONLY				OBS ONLY
HIL (C)		300	3	-	300	90	300	17000	600	13	1200	30000		252					
HIL (D)			-	-	3000	900	3600	240000	1500	180	6000	400000							
RANGE OF VALUES																	6.5-8.5		
Practical Quantitation Limit or Limit of Reporting (PQL)		0.05			4	0.4	1	1	1	0.1	1	1	1	7	10	1			
112	DUPLICATE												[NT]	[NT]	[NT]	[NT]	8.7	[NT]	
113	10m in front of BC 2	<0.05	<0.5	<0.05	<4	<0.4	5	5	79	<0.1	3	12	[NT]	[NT]	[NT]	[NT]	7.9	[NT]	
114	10m in front of BC 4	<0.05	<0.5	<0.05	<4	<0.4	3	2	86	<0.1	2	12	[NT]	[NT]	[NT]	[NT]	7.9	[NT]	
115	10m in front of BC 5	<0.05	<0.5	<0.05	<4	<0.4	3	2	7	<0.1	2	11	[NT]	[NT]	[NT]	[NT]	7.7	[NT]	
116	Sediment - Basin 5	<0.05	<0.5	<0.05	<4	<0.4	5	16	14	<0.1	5	23	[NT]	[NT]	[NT]	[NT]	7	[NT]	
119	Mound – Range 1 east	0.05	<0.5	0.05	4	<0.4	14	12	28	<0.1	5	43	[NT]	[NT]	[NT]	[NT]	7.8	[NT]	

TABLE 16 SOIL & SEDIMENT RESULTS 500m															DATE: 20 JUNE 2023			
Sample ID	Sample Location	PAH-Total	PAH-B(a)PTEQ	PAH-B(a)P	Arsenic	Cadmium	Chromium	Copper	Lead	Mercury	Nickel	Zinc	Tin	Anti-mony	Iron	CEC	pH	Clay in Soil <2µm
	Units	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	meq/100g	pH Units	% W/W
EIL from WCMP				(ESL) 0.7	100	-	414	132	1113	-	34	190	OBS ONLY	-	OBS ONLY			OBS ONLY
HIL (C)		300	3	-	300	90	300	17000	600	13	1200	30000		252				
HIL (D)			-	-	3000	900	3600	240000	1500	180	6000	400000						
RANGE OF VALUES																		
Practical Quantitation Limit or Limit of Reporting (PQL)		0.05			4	0.4	1	1	1	0.1	1	1	1	7	10	1		6.5 - 8.5
201	Bushland 1 - South	<0.05	<0.5	<0.05	<4	<0.4	11	2	11	<0.1	2	7	[NT]	[NT]	[NT]	[NT]	5.5	[NT]
202	Bushland 2-West 1	<0.05	<0.5	<0.05	<4	<0.4	13	1	16	<0.1	3	7	[NT]	[NT]	[NT]	[NT]	5.6	[NT]
203	Bushland 3- West 2	<0.05	<0.5	<0.05	4	<0.4	36	<1	17	<0.1	3	6	[NT]	[NT]	[NT]	[NT]	5.6	[NT]
204	Bushland 4 -East	<0.05	<0.5	<0.05	<4	<0.4	19	2	14	<0.1	4	7	[NT]	[NT]	[NT]	[NT]	5.4	[NT]
204	DUPLICATE	<0.05	<0.5	<0.05	<4	<0.4	20	2	16	<0.1	4	8	[NT]	[NT]	[NT]	[NT]	-	[NT]
205	Bushland 5- North	<0.05	<0.5	<0.05	<4	<0.4	18	2	11	<0.1	3	8	[NT]	[NT]	[NT]	-	5.4	
210	Ad. Range Floor 2	0.4	<0.5	0.07	<4	<0.4	16	23	64	<0.1	4	50	[NT]	[NT]	[NT]	[NT]	7.2	[NT]
210	DUPLICATE	-	-	-	-	-	-	-	-	-	-	-	[NT]	[NT]	[NT]	-	7.3	
211	Range floor 0-50m	<0.05	<0.5	<0.05	<4	<0.4	9	5	11	<0.1	3	13	[NT]	[NT]	[NT]	[NT]	7.6	[NT]
212	Range floor 50-100m	0.07	<0.5	0.07	<4	<0.4	7	17	99	<0.1	4	45	[NT]	[NT]	[NT]	[NT]	7.6	[NT]
213	Range floor 100-150m	<0.05	<0.5	<0.05	<4	<0.4	18	12	220	<0.1	3	6	[NT]	[NT]	[NT]	[NT]	6.9	[NT]
214	Range floor 150-200m	<0.05	<0.5	<0.05	<4	<0.4	16	7	30	<0.1	3	8	[NT]	[NT]	[NT]	[NT]	6.7	[NT]
215	Range floor 200-285m	<0.05	<0.5	<0.05	<4	<0.4	13	30	270	<0.1	3	20	[NT]	[NT]	[NT]	[NT]	6.2	[NT]

TABLE 16 SOIL & SEDIMENT RESULTS 500m															DATE: 20 JUNE 2023			
Sample ID	Sample Location	PAH-Total	PAH-B(a)PTEQ	PAH-B(a)P	Arsenic	Cadmium	Chromium	Copper	Lead	Mercury	Nickel	Zinc	Tin	Anti-mony	Iron	CEC	pH	Clay in Soil <2µm
	Units	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	meq/100g	pH Units	% W/W
EIL from WCMP				(ESL) 0.7	100	-	414	132	1113	-	34	190	OBS ONLY	-	OBS ONLY			OBS ONLY
HIL (C)		300	3	-	300	90	300	17000	600	13	1200	30000		252				
HIL (D)			-	-	3000	900	3600	240000	1500	180	6000	400000						
RANGE OF VALUES																		
Practical Quantitation Limit or Limit of Reporting (PQL)		0.05			4	0.4	1	1	1	0.1	1	1	1	7	10	1		6.5 - 8.5
216	Range floor 285-350m	<0.05	<0.5	<0.05	<4	<0.4	15	2	13	<0.1	3	6	[NT]	[NT]	[NT]	[NT]	6.6	[NT]
217	Range floor 350-500m	<0.05	<0.5	<0.05	<4	<0.4	16	1	11	<0.1	2	4	[NT]	[NT]	[NT]	[NT]	6.1	[NT]
217	DUPLICATE	-	-	-	-	-	-	-	-	-	-	-	[NT]	[NT]	[NT]	[NT]	6.2	[NT]
218	Ad. Range Floor 6	<0.05	<0.5	<0.05	<4	<0.4	16	2	11	<0.1	3	6	[NT]	[NT]	[NT]	[NT]	5.9	[NT]
218	DUPLICATE	<0.05	<0.5	<0.05	<4	<0.4	14	2	12	<0.1	2	5	[NT]	[NT]	[NT]	[NT]	-	[NT]
219	Ad. Range Floor 3	<0.05	<0.5	<0.05	<4	<0.4	16	4	31	<0.1	3	6	[NT]	[NT]	[NT]	[NT]	6.7	[NT]
221	Int Mound 1- 50m	<0.05	<0.5	<0.05	10	<0.4	14	6	36	<0.1	2	16	[NT]	[NT]	[NT]	[NT]	6.7	[NT]
222	Int Mound 2- 100m	<0.05	<0.5	<0.05	4	<0.4	10	27	940	<0.1	2	10	[NT]	[NT]	[NT]	[NT]	7.5	[NT]
223	Int Mound 3- 200m	<0.05	<0.5	<0.05	<4	<0.4	7	54	3800	<0.1	3	17	[NT]	[NT]	[NT]	[NT]	8.2	[NT]
224	Int Mound 4- 250m	<0.05	<0.5	<0.05	<4	<0.4	7	21	400	<0.1	2	13	[NT]	[NT]	[NT]	[NT]	8.2	[NT]
225	Int Mound 5- 300m	<0.05	<0.5	<0.05	<4	<0.4	7	39	460	<0.1	2	13	[NT]	[NT]	[NT]	[NT]	8.2	[NT]
226	Int Mound 6- 385m	<0.05	<0.5	<0.05	<4	<0.4	7	14	940	<0.1	2	11	[NT]	[NT]	[NT]	[NT]	5.6	[NT]
227	Main Butt -West	<0.05	<0.5	<0.05	<4	<0.4	2	<1	12	<0.1	<1	3	[NT]	[NT]	[NT]	[NT]	6.9	[NT]

TABLE 16 SOIL & SEDIMENT RESULTS 500m															DATE: 20 JUNE 2023			
Sample ID	Sample Location	PAH-Total	PAH-B(a)PTEQ	PAH-B(a)P	Arsenic	Cadmium	Chromium	Copper	Lead	Mercury	Nickel	Zinc	Tin	Anti-mony	Iron	CEC	pH	Clay in Soil <2µm
	Units	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	meq/100g	pH Units	% W/W
EIL from WCMP				(ESL) 0.7	100	-	414	132	1113	-	34	190	OBS ONLY	-	OBS ONLY			OBS ONLY
HIL (C)		300	3	-	300	90	300	17000	600	13	1200	30000		252				
HIL (D)			-	-	3000	900	3600	240000	1500	180	6000	400000						
RANGE OF VALUES																		
Practical Quantitation Limit or Limit of Reporting (PQL)		0.05			4	0.4	1	1	1	0.1	1	1	1	7	10	1		6.5 - 8.5
228	Main Butt - Central	<0.05	<0.5	<0.05	<4	<0.4	<1	2	96	<0.1	<1	4	[NT]	[NT]	[NT]	[NT]	6.8	[NT]
228	DUPLICATE	-	-	-	-	-	-	-	-	-	-	-	[NT]	[NT]	[NT]	[NT]	6.8	[NT]
229	Main Butt - East	<0.05	<0.5	<0.05	<4	<0.4	3	2	100	<0.1	3	8	[NT]	[NT]	[NT]	[NT]	7	[NT]
231	10m in front - Mound 1	<0.05	<0.5	<0.05	<4	<0.4	10	5	19	<0.1	2	12	[NT]	[NT]	[NT]	[NT]	7.1	[NT]
232	10m in front - Mound 2	<0.05	<0.5	<0.05	<4	<0.4	10	16	130	<0.1	3	11	[NT]	[NT]	[NT]	[NT]	7.4	[NT]
232	DUPLICATE	<0.05	<0.5	<0.05	<4	<0.4	8	24	210	<0.1	2	10	[NT]	[NT]	[NT]	[NT]	-	[NT]
233	10m in front - Mound 3	0.4	<0.5	0.05	4	<0.4	13	46	600	<0.1	3	14	[NT]	[NT]	[NT]	[NT]	7.2	[NT]
234	10m in front - Mound 4	<0.05	<0.5	<0.05	<4	<0.4	20	3	18	<0.1	3	7	[NT]	[NT]	[NT]	[NT]	6.6	[NT]
235	10m in front - Mound 5	<0.05	<0.5	<0.05	<4	<0.4	13	6	52	<0.1	2	7	[NT]	[NT]	[NT]	[NT]	6.8	[NT]
236	10m in front - Mound 6	<0.05	<0.5	<0.05	<4	<0.4	18	4000	2500	<0.1	3	170	[NT]	[NT]	[NT]	[NT]	6.4	[NT]
237	10m - butt - West	<0.05	<0.5	<0.05	<4	<0.4	13	4300	190	<0.1	9	230	[NT]	[NT]	[NT]	[NT]	6.9	[NT]
238	10m- butt - Central	<0.05	<0.5	<0.05	<4	<0.4	12	260	410	<0.1	2	20	[NT]	[NT]	[NT]	[NT]	6.3	[NT]
239	10m - butt - East	<0.05	<0.5	<0.05	4	<0.4	13	20	67	<0.1	2	14	[NT]	[NT]	[NT]	[NT]	6	[NT]

TABLE 16 SOIL & SEDIMENT RESULTS 500m															DATE: 20 JUNE 2023			
Sample ID	Sample Location	PAH-Total	PAH-B(a)PTEQ	PAH-B(a)P	Arsenic	Cadmium	Chromium	Copper	Lead	Mercury	Nickel	Zinc	Tin	Anti-mony	Iron	CEC	pH	Clay in Soil <2µm
	Units	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	meq/100g	pH Units	% W/W
EIL from WCMP				(ESL) 0.7	100	-	414	132	1113	-	34	190	OBS ONLY	-	OBS ONLY			OBS ONLY
HIL (C)		300	3	-	300	90	300	17000	600	13	1200	30000		252				
HIL (D)			-	-	3000	900	3600	240000	1500	180	6000	400000						
RANGE OF VALUES																	6.5 - 8.5	
Practical Quantitation Limit or Limit of Reporting (PQL)		0.05			4	0.4	1	1	1	0.1	1	1	1	7	10	1		
239	DUPLICATE	-	-	-	-	-	-	-	-	-	-	-	[NT]	[NT]	[NT]	[NT]	6	[NT]
241	Sed Basin 2 500 West	0.07	<0.5	0.07	<4	<0.4	4	44	10	<0.1	13	68	[NT]	[NT]	[NT]	[NT]	7.7	[NT]
241	DUPLICATE	<0.05	<0.5	<0.05	6	<0.4	7	34	9	<0.1	7	41	[NT]	[NT]	[NT]	[NT]	-	[NT]
243	Sed Basin 3 500 East	<0.05	<0.5	<0.05	<4	<0.4	5	9	13	<0.1	3	19	[NT]	[NT]	[NT]	[NT]	6.9	[NT]
245	DUPLICATE	<0.05	<0.5	<0.05	<4	<0.4	15	4	15	<0.1	4	13	[NT]	[NT]	[NT]	[NT]	6.8	[NT]
240	Gravel container area	<0.05	<0.5	<0.05	<4	<0.4	6	4	2	<0.1	3	15	[NT]	[NT]	[NT]	[NT]	7.9	[NT]
253	Sediment Basin 1	<0.05	<0.5	<0.05	<4	<0.4	10	7	10	<0.1	3	19	[NT]	[NT]	[NT]	[NT]	7.3	[NT]
253	DUPLICATE	-	-	-	-	-	-	-	-	-	-	-	[NT]	[NT]	[NT]	[NT]	7.3	[NT]
258	Sedi. below Basin 3	<0.05	<0.5	<0.05	4	<0.4	16	4	17	<0.1	4	26	[NT]	[NT]	[NT]	[NT]	6.4	[NT]
258	Sediment - Basin 1	-	-	-	-	-	-	-	-	-	-	-	[NT]	[NT]	[NT]	[NT]	6.2	[NT]
265	Sed Basin 4 – car park	<0.05	<0.5	<0.05	5	<0.4	24	22	29	<0.1	9	51	[NT]	[NT]	[NT]	[NT]	6.2	[NT]

TABLE 17 SOIL & SEDIMENT RESULTS 800m															DATE: 20 JUNE 2023			
Sample ID	Sample Location	PAH-Total	PAH-B(a)PTEQ	PAH-B(a)P	Arsenic	Cadmium	Chromium	Copper	Lead	Mercury	Nickel	Zinc	Tin	Antimony	Iron	CEC	pH	
	Units	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	mg/kg	meq/100g	pH Units	
EIL from WCMP				(ESL) 0.7	100	-	414	132	1113	-	34	190	OBS ONLY	-	OBS ONLY			
HIL (C)		300	3	-	300	90	300	17000	600	13	1200	30000		252				
HIL (D)			-	-	3000	900	3600	240000	1500	180	6000	400000						
RANGE OF VALUES																	6.5-8.5	
Practical Quantitation Limit or Limit of Reporting (PQL)		0.05			4	0.4	1	1	1	0.1	1	1	1	7	10	1		
301	Bullet catcher 2	<0.05	<0.5	<0.05	<4	<0.4	4	32	3300	<0.1	1	9	[NT]	[NT]	[NT]	[NT]	9.2	
302	Bullet catcher 4	<0.05	<0.5	<0.05	<4	<0.4	7	48	5900	<0.1	3	14	[NT]	[NT]	[NT]	[NT]	9.1	
303	Above bullet C 3	<0.05	<0.5	<0.05	20	<0.4	25	190	6100	<0.1	3	31	[NT]	[NT]	[NT]	[NT]	7.8	
303	DUPLICATE	<0.05	<0.5	<0.05	14	<0.4	19	7800	2800	<0.1	4	330	[NT]	[NT]	[NT]	[NT]		
304	Between BC 4-5	<0.05	<0.5	<0.05	<4	<0.4	1	11	520	<0.1	<1	9	[NT]	[NT]	[NT]	[NT]	7.6	
305	Butt under BC 1	<0.05	<0.5	<0.05	<4	<0.4	<1	<1	57	<0.1	<1	4	[NT]	[NT]	[NT]	[NT]	7.7	
306	Butt under BC 6	<0.05	<0.5	<0.05	<4	<0.4	5	10	690	<0.1	2	8	[NT]	[NT]	[NT]	[NT]	7.8	
307	Mantlet West	<0.05	<0.5	<0.05	<4	<0.4	8	4	100	<0.1	2	8	[NT]	[NT]	[NT]	[NT]	7	
308	Mantlet Central	<0.05	<0.5	<0.05	<4	<0.4	8	5	160	<0.1	2	9	[NT]	[NT]	[NT]	[NT]	7.1	
308	DUPLICATE												[NT]	[NT]	[NT]	[NT]	7	
309	Mantlet East	<0.05	<0.5	<0.05	<4	<0.4	8	7	99	<0.1	3	8	[NT]	[NT]	[NT]	[NT]	6.9	
310	10m Mantlet West	<0.05	<0.5	<0.05	<4	<0.4	13	32	500	<0.1	3	17	[NT]	[NT]	[NT]	[NT]	7.7	
311	10m Mantlet Cent.	<0.05	<0.5	<0.05	<4	<0.4	10	91	670	<0.1	2	20	[NT]	[NT]	[NT]	[NT]	7.7	
312	10m Mantlet East	<0.05	<0.5	<0.05	<4	<0.4	10	14	150	<0.1	2	10	[NT]	[NT]	[NT]	[NT]	7.9	
313	Bench West	<0.05	<0.5	<0.05	4	<0.4	14	140	1200	<0.1	3	29	[NT]	[NT]	[NT]	[NT]	7.7	

TABLE 17 SOIL & SEDIMENT RESULTS 800m															DATE: 20 JUNE 2023		
314	Bench Central	<0.05	<0.5	<0.05	7	<0.4	13	410	2200	<0.1	4	42	[NT]	[NT]	[NT]	[NT]	7.8
314	DUPLICATE	<0.05	<0.5	<0.05	7	<0.4	14	1100	1900	<0.1	4	69	[NT]	[NT]	[NT]	[NT]	
315	Bench East	1.9	<0.5	0.3	6	<0.4	12	15000	3000	<0.1	5	530	[NT]	[NT]	[NT]	[NT]	7.9
316	Rear of Butt	0.05	<0.5	0.05	4	<0.4	22	7	33	<0.1	2	6	[NT]	[NT]	[NT]	[NT]	7.7
317	Area over store	<0.05	<0.5	<0.05	<4	<0.4	12	17	230	<0.1	3	12	[NT]	[NT]	[NT]	[NT]	7.4
318	SW culvert upper	<0.05	<0.5	<0.05	5	<0.4	14	13	73	<0.1	3	21	[NT]	[NT]	[NT]	[NT]	7.1
319	SW culvert lower	<0.05	<0.5	<0.05	<4	<0.4	8	7	54	<0.1	2	13	[NT]	[NT]	[NT]	[NT]	6.8
320	Rear channel upper	<0.05	<0.5	<0.05	15	<0.4	12	52	310	0.1	2	24	[NT]	[NT]	[NT]	[NT]	6.7
321	Rear channel lower	<0.05	<0.5	<0.05	9	<0.4	9	17	110	<0.1	2	17	[NT]	[NT]	[NT]	[NT]	6.9
322	Basin 7 (off 800)	<0.05	<0.5	<0.05	<4	<0.4	3	<1	5	<0.1	1	7	[NT]	[NT]	[NT]	[NT]	6.6
322	Duplicate												[NT]	[NT]	[NT]	[NT]	6.4
323	Sediment Gallery	2.9	0.7	0.5	21	3	38	200	2400	<0.1	14	2300	[NT]	[NT]	[NT]	[NT]	6.9

TABLE 18 WATER RESULTS – SHRSC (800M, 50M& 500M) & SURROUNDS														DATE: 15 JUNE 2023		
Sample ID	LOCATION	pH	TSS	Turbidity	Total N	Ammonia as N	DO	Phosphate as P	Phosphorus	Arsenic	Chromium	Nickel	Lead	Antimony	Copper	Zinc
					OBS ONLY		OBS ONLY		OBS ONLY							
	ANZECC 2000 PFWS/NEPM 2013 GIL				0.25	0.9		0.015	0.2	13	3.3	11	3.4	9	1.4	8
	ANZECC 2000 RWQG				0.25	10				50	50	100	50	-	1000	5000
Units		pH Units	TSS	NTU	mg/L	mg/L	mg/L	mg/L	mg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L	µg/L
Practical Quantitation Limit or Limit of Reporting Test (PQL)					0.1	0.005	0.1	0.005	0.05	1	1		1		1	1
117	Basin 5 – 50m	7.6	<5	0.6	0.2	<0.005	7.8	<0.005	<0.05	<1	<1	<1	<1	7	<1	2
117	Duplicate	7.7	[NT]	[NT]	0.2	<0.005	[NT]	<0.005	<0.05	<1	<1	<1	<1	7	<1	1
242	Basin 2 (500m West)	7.7	<5	0.3	0.3	<0.005	7.9	<0.005	<0.05	<1	<1	<1	<1	8	<1	2
242	Basin 2 DUPLICATE									[NT]	[NT]	[NT]	[NT]	[NT]	[NT]	[NT]
244	Basin 3 (500m East)	8.3	<5	3.7	0.3	<0.005	8	<0.005	<0.05	<1	<1	<1	<1	2	1	1
252	Basin 1 – 200m	7.9	<5	1.6	0.4	<0.005	8.1	<0.005	<0.05	<1	<1	<1	<1	<1	<1	3
266	Basin 4 (Car Park)	6.9	<5	4.2	0.1	<0.005	7.9	<0.005	<0.05	<1	<1	<1	<1	<1	<1	2
331	Basin 7 – off 800m	6.3	25	44	0.3	0.024	8.2	<0.005	<0.05	<1	1	<1	3	<1	<1	6